

JOB _____

LOW PROFILE TRAY DELIVERY CARTS (One Door, Two Trays per Slide)





Item Number: DXTS2T1DLC10 Shown with optional top rail and menu holder

Application

Tray Delivery Cart(s) for insulated base, wax base or induction base systems and are ideal for room service concept. This cart is compatible with all Dinex[®] products for 15" x 20", 14" x 18", 12" x 19" and 12" x 20" trays. These models accommodates two trays per slide.

Construction

Carts are constructed with 304 No. 3 finish stainless steel, all welds are ground and polished. Meal delivery carts are heavy duty stainless steel construction as follows:

Тор	20 gauge, 304 No. 4 Finish
End/Back	
Panels	20 gauge, 304 No. 4 Finish
Base	20 gauge, 304 No. 4 Finish
Door Front	22 gauge, 304 No. 4 Finish
Door Back	22 gauge, 304 No. 4 Finish

Top and base are welded to body of the unit for added strength. All exterior welds are ground and polished. Chassis has 14 gauge stainless steel caster channels. The 1.125" thick, non-marking, polyethylene heavy-duty wrap around bumpers are mounted at full perimeter of the base. Two vertical push handles are front mounted for optimal ergonomic position when pushing the cart. Vents on three sides are standard.

Cam Action Style Door

The door on all models are doublewalled and insulated. The free floating door has a full 270° door swing. Closure is by gravity lock device, which retains the door in both the 270° open position as well as the 0° closed position.

Adjustable Tray Slides

Stainless steel tray slides, 20 gauge are positioned at specified vertical spacing and removable for cleaning. Slides are field adjustable to accommodate 15" x 20", 14" x 18", 12" x 19", and 12" x 20" trays.

Item Numbers

DXTS2T1DLC10
DXTS2T1DLC12
DXTS2T1DLC14



Casters

Four 6" Colson Performa casters, 2 swivel w/brakes and 2 fixed all with precision sealed ball bearings are standard. Casters are plate mounted and bolted to the base.

Standard Features


- 6" Performa Casters w/Precision sealed ball bearing
- 2-locking casters
- Vertical push handles
- Full length door handle


Warranty


One year parts and labor.



LOW PROFILE TRAY DELIVERY CARTS (One Door, Two Trays per Slide)









Items and Dimensions

ITEM NUMBER	MODEL NUMBER	LENGTH	DEPTH	HEIGHT	SHIP WEIGHT	SHIP CUBE	TRAY SPACING	TRAY CAPACITY
DXTS2T1DLC10	TS2T1DLC10	30" (76.2cm)	33.5" (85.1cm)	49.5" (125.7cm)	233 lb. (106kg)	31.6	7.0" (18cm)	10
DXTS2T1DLC12	TS2T1DLC12	30" (76.2cm)	33.5" (85.1cm)	49.5" (125.7cm)	233 lb. (106kg)	31.6	5.875" (15cm)	12
DXTS2T1DLC14	TS2T1DLC14	30" (76.2cm)	33.5" (85.1cm)	49.5" (125.7cm)	233 lb. (106kg)	31.6	5.0" (13cm)	14

Optional Accessories

Casters

- Polyurethane (8")
- Performa (8")
- 6" Carpet casters
- 8" Carpet casters

Top Rail

- 2.35" high (6.5cm), 3-sided
- 2.35" high (6.5cm), 4-sided

Other Options

- Floor Drain
- Menu Card Holder
- Transport Latch
- Tow Hitch
- Wall Saver (Corner Bumper)



Please confirm that you have the most current specification sheet by visiting www.dinex.com. Dinex[®] reserves the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.



www.dinex.com