

Deluxe Installation Kits & Hose Assemblies with Safety Quik™ Quick-Disconnect Protection Valve & Single SwivelMAX™


Product Part Numbers - Order Using Part Numbers Listed Below

| Configuration | Inside Dia. | LENGTH | | | | |
|-----------------|-------------|---------------|---------------|---------------|---------------|---------------|
| | | 24" | 36" | 48" | 60" | 72" |
| DELUXE KIT* | 1/2" | 1650KITCFS24 | 1650KITCFS36 | 1650KITCFS48 | 1650KITCFS60 | 1650KITCFS72 |
| HOSE ASSEMBLY ♦ | | 1650BPCFS24 | 1650BPCFS36 | 1650BPCFS48 | 1650BPCFS60 | 1650BPCFS72 |
| DELUXE KIT* | 3/4" | 1675KITCFS24 | 1675KITCFS36 | 1675KITCFS48 | 1675KITCFS60 | 1675KITCFS72 |
| HOSE ASSEMBLY ♦ | | 1675BPCFS24 | 1675BPCFS36 | 1675BPCFS48 | 1675BPCFS60 | 1675BPCFS72 |
| DELUXE KIT* | 1" | 16100KITCFS24 | 16100KITCFS36 | 16100KITCFS48 | 16100KITCFS60 | 16100KITCFS72 |
| HOSE ASSEMBLY ♦ | | 16100BPCFS24 | 16100BPCFS36 | 16100BPCFS48 | 16100BPCFS60 | 16100BPCFS72 |

BTU Flow Capacity (Flow rating BTU 0.64 SP. GR. @ 0.5 inch WC pressure drop)

| Part # | Inside Dia. | LENGTH | | | | | |
|------------|-------------|---------|---------|---------|---------|---------|---------|
| | | 12" | 24" | 36" | 48" | 60" | 72" |
| 1650BPCFS | 1/2" | 92,000 | 81,000 | 72,000 | 63,000 | 56,000 | 51,000 |
| 1675BPCFS | 3/4" | 242,000 | 216,000 | 203,000 | 167,000 | 147,000 | 130,000 |
| 16100BPCFS | 1" | 396,000 | 385,000 | 353,000 | 310,000 | 274,000 | 260,000 |

Technical Drawing



Approvals & Certifications



NSF International Criteria C-2, Special Equipment and/or Devices

Component



UL 567, Pipe Connectors for Flammable and Combustible Liquids and LP-Gas



ANSI Z21.69 / CSA 6.16 - Connectors for Moveable Gas Appliances

US

ANSI Z21.41 / CSA 6.9 - Quick-Disconnect Devices For Use With Gas Fuel

ANSI Z21.15 / CGA 9.1 - Manually Operated Gas Valves for Appliances, Appliance Connector Valves, and Hose End Valves

Meets requirements of ANSI Z223.1 / NFPA 54 - National Fuel Gas Code

Refer to catalog page 23 for additional approvals & certifications and Dormont gas connector limited lifetime warranty

SwivelMAX and Safety Quik are not for use in temperatures less than 32°F



Features & Specifications

THE DORMONT BLUE HOSE:

Tubing Annealed, 304 stainless steel (ASTM A240)
 Braiding Multi-strand, 304 stainless steel wire
 Coating Antimicrobial (patent #6,742,815) PVC, melts at 350° F, coating will not

hold a flame; blue color indicates braided connector
 End Fittings Carbon steel; zinc and yellow dichromate coating
 Stress Guard 360° rotation of end fittings at both ends before and after installation (patent pending)

SWIVEL MAX: Aluminum body, brass threaded end fittings
 Movement 360° multi-plane spherical rotation
 Patent # US patent 5,178,422 and 4,615,547; Canada patent 2,079,825

THE SAFETY QUIK-Quick Disconnect Protection Valve:

Quick-Disconnect Brass body, carbon steel safety sleeve; Flat face, push-to-connect Protection Valve
 quick-disconnect; Full port, brass gas ball valve
 Thermal Shut-off Shuts off gas flow when internal temperatures exceed 350° F
 Patent # US patent 5,383,492

* DELUXE KITS INCLUDE:

Elbow Malleable iron - 1 included
 Restraining Cable PVC coated, carbon steel, multi-strand cable and mounting hardware required for caster-mounted installations

HOSE ASSEMBLIES

♦ INCLUDE: Hose assembly and (1) elbow

DEMAND THE DIFFERENCE!

1-800-DORMONT
Dormont
 www.dormont.com