



"Your Solutions Partner"

Specifications

F.O.B. Sedalia, Missouri 65301



Heat-in-Base

Sliding Doors



Skeleton Unit

3-Bar Tray Slides



Solid Tray Slides

AGENCY LISTINGS:



DUKE MANUFACTURING CO.
2305 N. Broadway
St. Louis, MO 63102

800.735.3853 Toll Free
314.231.1130 In Missouri
314.231.5074 Fax
www.dukemfg.com

Approval Stamp(s):

PROJECT INFORMATION:

PROJECT: _____
ITEM: _____
QUANTITY: _____

MODEL:

Thurmaduke Serving Systems Accessories

- **HTD-BASE-M** Heat-in-Base modular unit
- **328PG/SS-OP** Sliding doors - Operator's side, S/S or paint grip
- **328PG/SS-CU** Sliding doors - Customer's side, S/S or paint grip
- **TS380-PG/SS** Skeleton unit - S/S or paint grip
- **TS381-PG/SS** End return - S/S or paint grip
- **TS3BTS-HD** Tubular tray slides, S/S, hinged brackets
- **TS3BTS-FX** Tubular tray slides, S/S, fixed brackets
- **TSSOLID-HD** Solid tray slides, S/S, hinged brackets
- **TSSOLID-FX** Solid tray slides, S/S, fixed brackets

HEAT-IN-BASE MODULAR UNIT:

- For hot food and solid top units
- Accommodates (4) 6"D pans; (6) 4"D pans; (12) 2"D pans
- Includes electric outlet in cabinet base when ordered with steamtable
- Available as stand-alone retrofit for hot food and solid top units already in field
- (2) units can be used in 5- or 6-well units.

SKELETON UNITS:

- Heavy gauge paint-grip or stainless steel
- Finish to match other units
- Available on legs only
- Specify length up to 132"

SLIDING DOORS:

- Double-wall, paint-grip or stainless steel
- Ball-bearing wheels on overhead tracks
- Lift out for easy cleaning
- Lock option at added charge

SOLID TRAY SLIDES:

- 18", 30", 32", 46", 60", 74", 88" standard lengths
- Heavy gauge stainless steel, stainless steel brackets
- (2) 1/8" high embossed rubbing tracks
- Special lengths available

3-BAR TRAY SLIDES:

- 18", 30", 32", 46", 60", 74", 88" standard lengths
- 1" diameter stainless steel tubes, ends capped
- Stainless steel brackets
- Special lengths available



**THURMADUKE SERVING SYSTEMS
ACCESSORIES**

- **HTD-BASE-M** Heat-in-Base modular unit
- **328PG/SS-OP** Sliding doors - Operator's side, S/S or paint grip
- **328PG/SS-CU** Sliding doors - Customer's side, S/S or paint grip
- **TS380-PG/SS** Skeleton unit - S/S or paint grip
- **TS381-PG/SS** End return - S/S or paint grip
- **TS3BTS-HD** Tubular tray slides, S/S, hinged brackets
- **TS3BTS-FX** Tubular tray slides, S/S, fixed brackets
- **TSSOLID-HD** Solid tray slides, S/S, hinged brackets
- **TSSOLID-FX** Solid tray slides, S/S, fixed brackets

Heat-in-Base Unit

Model	Left-to-Right		Height		Depth		Cutout Length		Cube Crated ft.	Weight	
	in.	cm	in.	cm	in.	cm	in.	cm		lbs.	kg
HTD-BASE-M	30	76.2	17	43.2	23	58.4	33-1/8	84.2	35.4	190	86.0

Skeleton Units

Model	Description
380-25	Front panel: 36" high, 12 lbs. per foot - must attach to adjacent unit
381-25	End panel: 32" wide, 36" high, 4" long, 20 lbs. w/6" legs

Sliding Doors - for Hot Food Units

Sliding Doors - for Solid Top, Cold Pan and Urn Stand Units

Model	Length		Door Height		Weight		Model	Length		Door Height		Weight	
	in.	cm	in.	cm	lbs.	kg		in.	cm	in.	cm	lbs.	kg
328-3	46	116.8	12	30.5	40	18.2	329-3	46	116.8	17	43.2	45	20.5
328-4	60	152.4	12	30.5	50	22.7	329-4	60	152.4	17	43.2	55	25.0
328-5	74	188.0	12	30.5	60	27.3	329-5	74	188.0	17	43.2	65	29.6
328-6	88	223.5	12	30.5	70	31.8	329-6	88	223.5	17	43.2	75	34.1

Tray Slides with Brackets - Fixed (FX) or Hinged (HD)

Freight Class - 85

Number of Sections	2		3		4		5		6	
	18" 45.7 cm	30" 76.2 cm	32" 81.3 cm	46" 116.8 cm	60" 152.4 cm	74" 188.0 cm	88" 223.5 cm			
TUBULAR - THREE 18 GAUGE STAINLESS STEEL TUBES (ENDS CAPPED) Weight: Approx. 7 lbs. (3.2) per foot (30.5 cm). 12"W / 30.5 cm										
SOLID - 16 GAUGE STAINLESS STEEL WITH TWO 1/8" (.13 cm) DIE-FORMED RUBBING TRACKS										
Weight: Approx. 12 lbs. (5.5 kg) per foot (30.5 cm). 12-1/4" / 31.1 cm Wide — Adds 13" (33.0 cm) to width of unit										
NO. OF BRACKETS PROVIDED FOR TUBULAR OR SOLID TRAY SLIDES	2	2	2	2	2	3	3			

NOTE: Each additional foot of Tray Slide includes required number of brackets. Maximum recommended span between brackets is five (5) feet (152.4 cm). For continuous Tray Slide, add one bracket at end of counter plus one bracket for each unit. Add one additional bracket for each unit that is longer than 60" (152.4 cm). SPECIFY IF BRACKETS ARE TO BE SHIPPED LOOSE OR MOUNTED TO TRAY SLIDE. If brackets are to be mounted, please supply a sketch (with measurements) of their exact locations.



"Your Solutions Partner"

DUKE MANUFACTURING CO.
2305 N. Broadway
St. Louis, MO 63102

800.735.3853 Toll Free
314.231.1130 In Missouri
314.231.5074 Fax
www.dukemfg.com

07/04

Specifications subject to change

Printed in U.S.A.
©2004, Duke Manufacturing Co.