



## **Specification Sheet**

#### **Short Form Specifications**

Eagle RedHots<sup>®</sup> Single-Tank Electric Fryer, model \_\_\_\_\_\_. All heavy gauge stainless steel construction. Stainless steel deep-drawn 10" x 14" fry tank is removable for cleaning or filtering. Snap action thermostat with indicator light, hi-limit safety control with reset button and indicator light. Two 4" x 11" nickel-plated fry baskets. Cast metal legs with nylon feet. 15-lb. fat capacity. All single-phase 60-Hz. Available in 120 volts/15 amps; 208 volts/19.8 amps; or 240 volts/22.9 amps.

Eagle RedHots<sup>®</sup> Double-Tank Electric Fryer, model \_\_\_\_\_\_. All heavy gauge stainless steel construction. Stainless steel deep-drawn 10<sup>°</sup> x 14<sup>°°</sup> fry tanks are removable for cleaning or filtering. Snap action thermostat with indicator light, hi-limit safety control with reset button and indicator light. Two 4<sup>°°</sup> x 11<sup>°°</sup> nickel-plated fry baskets per tank. Cast metal legs with nylon feet. 30-lb. fat capacity. All single-phase 60-Hz. Available in 208 volts/39.6 amps or 240 volts/45.8 amps.





single-tank model

double-tank model

#### **Options / Accessories**

Double fry basket
 2½" high legs
 Night cover

NOTE: INTENDED FOR OTHER THAN HOUSEHOLD USE. THESE COMMERCIAL APPLIANCES MUST BE INSTALLED WITHIN SURROUNDINGS AND VENTILATION REQUIREMENTS AS DICTATED BY NATIONAL AND/OR LOCAL CODE.

#### EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA Phone: 302-653-3000 • Fax: 302-653-2065 www.eaglegrp.com

Foodservice Division: Phone 800-441-8440 MHC/Retail Display Divisions: Phone 800-637-5100

For custom configuration or fabrication needs, contact our **SpecFAB® Division**. Phone: 302-653-3000 • Fax: 302-653-3091 • e-mail: specfab@eaglegrp.com

Item No.:	
Project No.:	
S.I.S. No.:	

### **RedHots® Electric Fryers**

#### MODELS: *EF10-120 EF102-240 307546 309781 EF10-120M 307543 309197 340859 EF10-240*

#### Fry tank

- All-stainless steel deep-drawn one-piece construction.
- 10" x 14" (254 x 356mm).
- Removable for easy cleaning or filtering of fat.
- Available are single-tank units with 15-lb. fat capacity, and double-tank unit with 30-lb. capacity.

#### Thermostat

- Snap action complete with indicator light provides for accurate temperature control.
- Temperature range: from 200°F to 375°F

#### Easy operation

- Fill with fat or shortening up to indicator line.
  Set thermostat dial for desired temperature. The amber light will stay on. When temperature is reached, the light will go
- out and cooking can start.After cooking, lift basket(s), hang and drain.

#### Hi limit safety control

- Provides total system shutdown in case of malfunction.
- · Complete with reset button and indicator light.

#### Heating elements

• Self-cleaning Incoloy<sup>®</sup> sheath for long life and high performance.

#### Fry baskets

- 4" x 11" (102 x 279mm) each.
- Heavy plated mesh construction.
- Two provided with single-tank models, four provided with double-tank model.
- Optional double fry baskets available.

#### **Design and Construction Features**

- Highly polished stainless steel body.
- Line cord and plug furnished on single tank models.
- Designed for direct field wiring on double tank models.

#### Warranty

Backed by a 1-YEAR Parts & Labor Warranty.





AUTOQUOTES


#### EG35.03 Rev. 05/12

Spec sheets available for viewing, printing or downloading from our online literature library at www.eaglegrp.com Eagle Foodservice Equipment, Eagle MHC, SpecFAB®, and Retail Display are divisions of Eagle Group. ©2012 by the Eagle Group **RedHots® Electric Fryers** 



Item No.: .	
Project No.: .	
S.I.S. No.: .	

# **RedHots® Electric Fryers**



### **Single-Tank Electric Fryers**

15-lb. (6.8 kg) fat capacity.

	NEMA performance *** –		width		depth		height *		weight		tank size				
model #	electrical data **	plug	french fries, raw-to-finish	in.	mm	in.	mm	in.	mm	lbs.	kg	in.	mm	in.	mm
EF10-120	120V, 15A, 1800W	5-15P	120V: 6 lbs.(2.7 kg)/hr	12″	305	19¼″′	489	10%″	270	31	14.1	10″	254	14″	356
EF10-120M	120V, 15A, 1800W	5-20P	120V: 6 lbs.(2.7 kg)/hr	12″	305	19¼″	489	10%″	270	31	14.1	10″	254	14″	356
EF10-240 ****	208V, 19.8A, 4125W 240V, 22.9A, 5500W	6-30P	208V: 20 lbs. (9.1 kg)/hr 240V: 30 lbs. (13.6 kg)/hr	12″	305	19¼‴	489	10%″	270	31	14.1	10″	254	14″	356
#EF10-120M fe	atures NEMA 5-20P plug.	which meets	Canadian approval.												

#### Double-Tank Electric Fryer

30-lb. (13.6 kg) total fat capacity

		performance *** -	width		depth		height *		weight		tank size			
model #	electrical data **	french fries, raw-to-finish	in.	mm	in.	mm	in.	mm	lbs.	kg	in.	mm	in.	mm
EF102-240 ****	208V, 39.6A, 8250W 240V, 45.8A, 11000W	208V: 40 lbs. (18.1 kg)/hr 240V: 60 lbs. (27.2 kg)/hr	25″	635	19¼″	489	105⁄8″	270	61	27.7	10″	254	14″	356

\* 10%" (270mm) working height, 15%" (391mm) overall height. Optional 2½" (64mm) legs available - part #309197.

\*\* Based on single-phase, 60-Hz electricity.

\*\*\* Double the performance for precooked convenience foods. Preheat to 350°F for 4½ minutes. Fryer performance is limited by the maximum available voltage in line.

\*\*\*\* 240-volt models can be used for 208V or 240V operation.

#### Accessories/Replacements for Electric Fryers

model #	description
307543	replacement basket, left side, for single-tank fryers only
307546	replacement basket, right side, for single-tank fryers only
309197	2¼" (57mm)-high legs, set of four
309781	double-fry basket, 8¼" x 9¼" x 4" (210 x 235 x 102mm)
340859	divider for double-tank fryer
361673 *	night cover *

\* Two covers required for #EF102-240 double-tank fryer.

#### EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA Phone: 302-653-3000 • Fax: 302-653-2065 www.eaglegrp.com

Foodservice Division: Phone 800-441-8440 MHC/Retail Display Divisions: Phone 800-637-5100



double-fry basket

Printed in U.S.A. ©2012 by Eagle Group Rev. 05/12

#### Spec sheets available for viewing, printing or downloading from our online literature library at www.eaglegrp.com

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.