

Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Eagle Cantilever Shelving System to consist of 14 gauge regular or NSF continuously seam-welded uprights, ceiling brackets, and single- or double-knob brackets. For use with either wire or solid shelving (sold separately). Heavy duty "C" brackets available in grey epoxy, stainless steel, or aluminum finish. Heavy duty crossbraces available in grey epoxy or nickel finish.

single knob heavy duty "C" bracket—shown with wire shelf mounted	
heavy-duty back-to-back upright	all-mounted cantilevered shelving shown with

Item No.:	
Project No.:	
S.I.S. No.:	

Cantilevered Shelving System —Heavy Duty Components

MODELS:

<i>□MMBC-K-*</i>	□ <i>MMDBC-K-*</i>	□ <i>MMBB-*</i>
<i>■MMNSBC-K-*</i>	□ <i>MMNSDBC-K-*</i>	□ <i>MMNSBB-*</i>
<i>■MMBCSS-K-*</i>	□ MMDBCSS-K-*	□ <i>MMBBSS*</i>
<i>■MMNSBCSS-K-*</i>	□ MMNSDBCSS-K-*	□ <i>MMNSBBSS*</i>
<i>□MMBC-K/A-*</i>	\square <i>MMDBC-K/A-*</i>	<i>□ MMBB/A-*</i>
<i>■MMNSBC-K/A-*</i>	□ MMNSDBC-K/A-*	<i>□ MMXB-*</i>
		□ M/M/YD_N_*

- * See charts on back page for complete model numbers.
- Designed with convenience in mind.
- Requires no post supports to get in the way, making shelf loading and unloading easier.
- For use with both wire and solid shelving.
- 100% usable shelving surface, from section to section, wall to wall, and front to back no posts to restrict stock placement.
- Infinite height adjustability no slots or keyholes to line up for leveling, and shimming is eliminated.
- Wall-mounted shelving requires no support from the floor
 floor area is therefore open and easily maintained.
- Finishes available include grey epoxy, stainless steel, and aluminum.
- Regular and NSF-approved components available.
- All components are made of heavy gauge material.
- Heavy-duty, rugged construction.

See Spec Sheet #EG01.45A for Uprights. See Spec Sheet #EG01.45B for Brackets.

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440 MHC/Retail Display Divisions: Phone 800-637-5100

For custom configuration or fabrication needs, contact our **SpecFAB® Division**. Phone: 302-653-3000 • Fax: 302-653-3091 • e-mail: specfab@eaglegrp.com



EG01.45C Rev. 09/10



Item No.: _	
Project No.: _	
S.I.S. No.: _	

Cantilevered Shelving System—Heavy Duty Components

HEAVY DUTY "C" BRACKETS

Heavy Duty Single Knob "C" Brackets

For dynamic loads. For use with wire or solid shelving. Available with flanges at top left or right. To order, add suffix "-L" (left bracket) or "-R" (right bracket) to model number. Example: MMBC-K-18-L

	ı	(GREY EPOXY			ST	AINLESS STEEL		ALUMINUM				
length		REGULAR NSF		weight		REGULAR	NSF	weight		REGULAR	NSF	wei	ght
in.	mm	model #	model #	lb.	kg	model #	model #	lb.	kg	model #	model #	lb.	kg
18″	457	MMBC-K-18	MMNSBC-K-18	3	1.4	MMBCSS-K-18	MMNSBCSS-K-18	2	0.9	MMBC-K/A-18	MMNSBC-K/A-18	1	0.5
21″	533	MMBC-K-21	MMNSBC-K-21	3	1.4	MMBCSS-K-21	MMNSBCSS-K-21	3	1.4	MMBC-K/A-21	MMNSBC-K/A-21	1	0.5
24"	610	MMBC-K-24	MMNSBC-K-24	3	1.4	MMBCSS-K-24	MMNSBCSS-K-24	3	1.4	MMBC-K/A-24	MMNSBC-K/A-24	2	0.9

Heavy Duty Double Knob "C" Brackets

For dynamic loads. For use with wire or solid shelving. With flanges on top left and right, these brackets support two adjoining shelves on a common upright.

			GREY EPOXY			ST/	AINLESS STEEL	ALUMINUM					
length		REGULAR NSF		weight		REGULAR	NSF	weight		REGULAR	NSF	wei	ght
in.	mm	model #	model #	lb.	kg	model #	model #	lb.	kg	model #	model #	lb.	kg
18″	457	MMDBC-K-18	MMNSDBC-K-18	4	1.8	MMDBCSS-K-18	MMNSDBCSS-K-18	3	1.4	MMDBC-K/A-18	MMNSDBC-K/A-18	2	0.9
21″	533	MMDBC-K-21	MMNSDBC-K-21	4	1.8	MMDBCSS-K-21	MMNSDBCSS-K-21	4	1.8	MMDBC-K/A-21	MMNSDBC-K/A-21	2	0.9
24"	610	MMDBC-K-24	MMNSDBC-K-24	5	2.3	MMDBCSS-K-24	MMNSDBCSS-K-24	4	1.8	MMDBC-K/A-24	MMNSDBC-K/A-24	2	0.9

HEAVY DUTY UPRIGHTS

Back-to-back, floor-to-ceiling, double-faced unitized uprights. Available in grey epoxy, stainless steel, or aluminum

finish. Regular or NSF-approved.

J	ı	GREY EPOXY			l S	TAINLESS STEEL	ALUMINUM				
height in. mm	REGULAR model #	NSF model #	weight lb. kg		REGULAR model #	NSF model #	we lb.	ight kg	REGULAR model #	R weigi	
48″ 1219	MMBB-4	MMNSBB-4	20	9.0	MMBBSS-4	MMNSBBSS-4	-11	5.0	MMBB/A-4	14	6.4
60″ 1524	MMBB-5	MMNSBB-5	25	11.3	MMBBSS-5	MMNSBBSS-5	24	10.9	MMBB/A-5	17	7.7
72″ 1829	MMBB-6	MMNSBB-6	30	13.6	MMBBSS-6	MMNSBBSS-6	28	12.7	MMBB/A-6	21	9.5
84" 2134	MMBB-7	MMNSBB-7	35	15.9	MMBBSS-7	MMNSBBSS-7	33	15.0	MMBB/A-7	24	10.9
96″ 2438	MMBB-8	MMNSBB-8	40	18.1	MMBBSS-8	MMNSBBSS-8	38	17.2	MMBB/A-8	28	12.7
108" 2743	MMBB-9	MMNSBB-9	45	20.4	MMBBSS-9	MMNSBBSS-9	42	19.1	MMBB/A-9	31	14.1
120″ 3048	MMBB-10	MMNSBB-10	50	22.7	MMBBSS-10	MMNSBBSS-10	47	21.3	MMBB/A-10	34	15.4
144″ 3658	MMBB-12	MMNSBB-12	60	27.2	MMBBSS-12	MMNSBBSS-12	57	25.9	MMBB/A-12	41	18.6

HEAVY DUTY CROSSBRACES

Adds to stability of unit. 1" (25mm)-wide 7-gauge steel.

	fi	ts	cros	sbrace	GREY E	POX	Υ	NICKEL			
shelf length		1.			weight			weight			
	in.	mm	in.	mm	model #	lb.	kg	model #	lb.	kg	
	36″	914	48″	1219	MMXB-48	2	0.9	MMXB-N-48	2	0.9	
	48″	1219	60″	1524	MMXB-60	3	1.4	MMXB-N-60	3	1.4	
	60″	1524	72″	1829	MMXB-72	4	1.8	MMXB-N-72	4	1.8	
	72"	1829	84″	2134	MMXB-84	5	2.3	MMXB-N-84	5	2.3	

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440

MHC/Retail Display Divisions: Phone 800-637-5100

Printed in U.S.A. ©2010 by Eagle Group

Rev. 09/10