

Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Eagle worktables. Spec-Master® series. model Top constructed of 14/304 stainless steel with 1½" roll on front, 4½" backsplash, and sides turned down 90°. Adjustable undershelf constructed of 18/304 stainless steel with marine edge. Top reinforced with stainless steel hat channels and sound deadened. Constructed with uni-lok® patented gusset system with the gussets recessed into the hat channels to reduce lateral movement. 1%"-diameter stainless steel legs, with stainless steel gussets and 1" stainless steel adjustable bullet feet.



	uni-lok® System No. 5,165,349)
worktable top sound-deadening tape between channel and top gusset recessed into channel reduces lateral movement that" channel frame 12-gauge gusset for 1%" leg is double-welded on backup plate and channel frame for added stability	hat channel and table top are welded together 12-gauge backup plate adds stability — indicates weld point

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440 MHC/Retail Display Divisions: Phone 800-637-5100

For	custom	configur	ation o	or fabrication	needs,	contact	our	SpecFAB	®	Division.
Phn	ne: 302-6	353-3000	Fax.	302-653-3091	• e-ma	il: specfa	h@e:	adlearn co	m	

Item No.: .	
Project No.: .	
S.I.S. No.: .	

Worktables with Backsplash and Stainless Steel Base with Undershelf —Spec-Master® Series

MODELS:			
□ <i>T2424SE-BS</i>	□ <i>T24108SE-BS</i>	□ <i>T3072SE-BS</i>	□ <i>T3660SE-BS</i>
□ <i>T2430SE-BS</i>	□ <i>T24120SE-BS</i>	□ <i>T3084SE-BS</i>	□ <i>T3672SE-BS</i>
□ <i>T2436SE-BS</i>	☐ T24132SE-BS	□ <i>T3096SE-BS</i>	□ <i>T3684SE-BS</i>
□ <i>T2448SE-BS</i>	☐ <i>T24144SE-BS</i>	□ <i>T30108SE-BS</i>	□ <i>T3696SE-BS</i>
□ <i>T2460SE-BS</i>	□ <i>T3030SE-BS</i>	□ <i>T30120SE-BS</i>	□ T36108SE-BS
☐ <i>T2472SE-BS</i>	☐ <i>T3036SE-BS</i>	□ <i>T30132SE-BS</i>	□ <i>T36120SE-BS</i>
□ <i>T2484SE-BS</i>	☐ <i>T3048SE-BS</i>	□ <i>T30144SE-BS</i>	□ T36132SE-BS
☐ <i>T2496SF-BS</i>	□ T3060SF-BS	□173648SF-BS	□ T36144SF-BS

Tabletop

- Patented uni-lok® gusset system (patent #5,165,349): gussets are recessed into hat channel, reducing lateral movement.
- Top reinforced with welded-on hat channel.
- Sound-deadened between top and channels.
- 4½" (114mm)-high 90° backsplash with 1" (25mm) turn at 90°.
- 1½" (38mm)-diameter 180° rolled edge on front. Ends are turned down 90°, providing for flush installations when required.
- 14 gauge type 304 polished stainless steel.

Adjustable Undershelf

- Heavy gauge stainless steel.
- Gusset welded to each corner.
- · Heavy duty marine edge design.

Legs—1%" (41mm)-diameter

- Tables 96" (2438mm) and longer come with six legs or more.
- Heavy gauge stainless steel.
- 1" (25mm) adjustable stainless steel feet.

Options / Accessories

Drawer	Duplex receptacles
Lock	Pot rack
Casters	Sink
Stainless steel bullet feet	Additional undershelf
Overshelves	Stabilizer Bar (for 30'
Power strip (for material handling)	and 36"-wide tables)

Certifications / Approvals







EG10.45C Rev. 01/12




Item No.:	
Project No.:	
S.I.S. No.:	

Worktables with Backsplash and Stainless Steel Base with Undershelf—Spec-Master® Series







	# of	width		length		weight	
model #	legs	in.	mm	in.	mm	lbs.	kg
T2424SE-BS	4	24"	610	24"	610	47	21.3
T2430SE-BS	4	24"	610	30"	762	53	24.0
T2436SE-BS	4	24"	610	36″	914	58	26.3
T2448SE-BS	4	24"	610	48″	1219	69	31.3
T2460SE-BS	4	24"	610	60″	1524	80	36.3
T2472SE-BS	4	24"	610	72″	1829	94	42.6
T2484SE-BS	4	24"	610	84″	2134	107	48.5
T2496SE-BS	6	24"	610	96″	2438	125	56.7
T24108SE-BS	6	24"	610	108″	2743	156	70.3
T24120SE-BS	6	24"	610	120″	3048	169	76.7
T24132SE-BS T24144SE-BS	8 8	24" 24"	610 610	132″ 144″	3353 3658	183 196	83.0 88.9
T3030SE-BS	4	30″	762	30″	762	55	24.9
T3036SE-BS	4	30″	762	36″	914	58	26.3
T3048SE-BS	4	30″	762	48″	1219	77	34.9
T3060SE-BS	4	30″	762	60″	1524	89	40.4
T3072SE-BS	4	30"	762	72″	1829	103	46.3
T3084SE-BS	4	30″	762	84"	2134	119	54.0
T3096SE-BS	6	30"	762	96″	2438	143	64.9
T30108SE-BS	6	30"	762	108″	2743	165	74.4
T30120SE-BS	6	30"	762	120″	3048	187	84.8
T30132SE-BS	8	30"	762	132"	3353	207	93.9
T30144SE-BS	8	30"	762	144"	3658	228	103.4
T3648SE-BS	4	36"	914	48"	1219	85	38.6
T3660SE-BS	4	36"	914	60″	1524	99	44.9
T3672SE-BS	4	36"	914	72"	1829	117	53.1
T3684SE-BS	4	36"	914	84"	2134	135	61.2
T3696SE-BS	6	36″	914	96″	2438	145	65.8
T36108SE-BS	6	36″	914	108″	2743	186	84.4
T36120SE-BS	6	36″	914	120″	3048	211	95.7
T36132SE-BS							
13013235-03	8	36"	914	132″	3353	238	108.0

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440

MHC/Retail Display Divisions: Phone 800-637-5100

Printed in U.S.A. ©2012 by Eagle Group

Rev. 01/12