

Edlund 28 lb and 56 lb Potato Peeling Machines

The Edlund Peelers are among the fastest potato peelers on the market, offering you the flavor of freshly peeled potatoes, with the speed and convenience of pre-prepared products. The peelers feature a compact footprint and are safe and simple to use. Because they are fast, they are very productive and use less staff time. They're built to last, with exceptional durability and outstanding reliability. How appealing!



EPP-28
28 lb Pedestal Mounted
Potato Peeler



EPP-28, 28 lb Potato Peeler with chamber door opened



EPP-56, 56 lb Potato Peeler with chamber door opened



EPP-56
56 lb Pedestal Mounted
Potato Peeler



Wall mounted controls. Each unit comes complete with a control box which is quickly and easily mounted to the wall, using a stainless steel bracket. The Peelers can be operated using the timer option - leaving the operator free for other jobs - or set to run continually.

FEATURES:

- Quick and easy to clean
- Designed for easy maintenance
- Robust stainless steel and cast alloy construction
- Rust-proof peeling plate
- Reversible rust-proof liners
- Dual position for waste outlet
- Quiet operation
- Energy efficient

SPECIFICATIONS:

MODEL #	DESCRIPTION	PRODUCT CODE	WEIGHT	OVERALL HEIGHT	PEELING CHAMBER HEIGHT
EPP-28	28 lb. Potato Peeler (stainless steel)	74101	105 lbs.(48 kg)	55" (1400 mm)	12" (305 mm)
EPP-56	56 lb. Potato Peeler (stainless steel)	74151	150 lbs. (68 kg)	53" (1360 mm)	11" (280 mm)

SPECIAL FEATURES

EASIER LOADING. A large hopper opening with a large stainless steel lip makes loading quick and easy. The lip is welded to the hopper, to eliminate difficult-to-clean gaps.

ENERGY EFFICIENT. Faster peeling means greater energy efficiency and lower water usage – leading to real cost savings.

EASIER CLEANING. The hygienic brushed stainless steel finish is easy to wash down. Water and waste drain efficiently from the smooth cylinder base aided by large cast paddles under the peeler plate. The lid and peeling plate are quick and easy to remove for cleaning.

QUIETER OPERATION. The motor and water inlet both run exceptionally quietly, resulting in an improved working environment, while the motor's cooler running temperature ensures optimum performance, efficiency and durability.

LONGER LIFE PEELING. The thickly gritted non-rusting cast aluminum peeler plate is designed to be rugged and offer a long service life. The carborundum non-rusting stainless steel cylinder liners can be reversed and relined for longer life and lower costs.

FAST PEELING. At up to 550 lbs. of potatoes peeled per hour, or almost a pound in 30 seconds, the EPP Peelers are among the fastest available, making them ideal wherever high volume potato peeling is required.

EPP-28		EPP-56	
Mounting:	Floor-mounted with low or high pedestal	Mounting:	Floor-mounted with low or high pedestal
Capacity:	28 lbs. (12 kg)	Capacity:	56 lbs. (25 kg)
Output:	264 lbs. (120 kg) hour	Output:	264 lbs. (250 kg) hour
Dimensions (H x W x D):	High pedestal 55" (1400 mm) x 21" (530 mm) x 25" (624 mm)	Dimensions (H x W x D):	High pedestal 54" (1360 mm) x 22" (564 mm) x 24" (725 mm)
Discharge height:	High pedestal 37" (930 mm)	Discharge height:	High pedestal 37" (930 mm)
Motor:	0.37 kW (0.5 h.p.)	Motor:	0.75 kW (1.0 h.p.)
Fuse rating:	15 A (1 phase), 5 A (3 phase)	Fuse rating:	15A (1 phase), 5A (3 phase)
Operator controls:	Control box (fixed to wall bracket) with on/off button, timer and continual run settings	Operator controls:	Control box (fixed to wall bracket) with on/off button, timer and continual run settings
Operator safety:	<ul style="list-style-type: none"> • Controls prevent automatic restart if power is cut • Low voltage P65 rated operator controls 	Operator safety:	<ul style="list-style-type: none"> • Controls prevent automatic restart if power is cut • Low voltage P65 rated operator controls
Special features:	<ul style="list-style-type: none"> • Quick and easy to clean • Designed for ease of maintenance • Hygienic, robust stainless steel and cast alloy construction • Rust-proof peeling plate and reversible rust-proof liners • Dual position for waste outlet • Quiet operation • Energy efficient 	Special features:	<ul style="list-style-type: none"> • Quick and easy to clean • Designed for ease of maintenance • Hygienic, robust stainless steel and cast alloy construction • Rust-proof peeling plate and reversible rust-proof liners • Dual position for waste outlet • Quiet operation • Energy efficient

Please note: Capacities are approximate and output may vary depending on the type and age of potatoes used



Edlund Company LLC, 159 Industrial Parkway, Burlington, VT 05401, USA 800-772-2126 www.edlundco.com

WARRANTY INFORMATION: THE EDLUND COMPANY WARRANTS THESE PRODUCTS TO BE FREE FROM DEFECTS IN MATERIAL AND WORKMANSHIP FOR A PERIOD OF ONE YEAR FROM DATE OF PURCHASE. THE COMPANY'S OBLIGATION UNDER THIS WARRANTY IS LIMITED TO REPAIRING OR REPLACING WITHOUT CHARGE ANY PART OR PARTS FOUND TO BE DEFECTIVE UNDER NORMAL USE. IT IS THE RESPONSIBILITY OF THE PURCHASER TO RETURN THE ENTIRE UNIT TO THE FACTORY, TRANSPORTATION CHARGES PREPAID. THIS WARRANTY DOES NOT COVER PARTS THAT MUST BE REPLACED UNDER NORMAL USE, INCLUDING KNIVES AND DRIVE GEARS ON CAN OPENERS. NO OTHER WARRANTY, WRITTEN OR VERBAL, IS AUTHORIZED BY THE COMPANY. WARRANTY INFORMATION OUTSIDE THE UNITED STATES MAY VARY, CONSULT YOUR DISTRIBUTOR.

06/11 EDL-1012