DNIC 2200E0

PNC 653703 🖵



## Libero Line Series Libero Point 3 freestanding self-ventilated downdraft cart

TEM #	
MODEL #	
IAME #	
SIS #	
NA#	



#### **Libero Line Series**

#### Libero Point 3 freestanding selfventilated downdraft cart

600064 (ELP3UX)

Libero Point 3 (Self-Ventilated Downdraft Cart)-208V/3ph/60Hz

# **Short Form Specification**

#### Item No.

The Libero Point 3 freestanding self-ventilated downdrat cart is built to accommodate up to three (3) electric countertop appliances from the Libero Line. Heavy duty stainless steel construction. Integrated radial fan (variable speed) ventilation system that reduces cooking odours from the cooking surfaces of the countertop Libero Line appliances. Air is filtered through the top of the appliance and released at the base. The self-contained air-filtration system is equipped with 3 filters, a dishwasher safe mechanical filter with a fine-meshed metal filter and a carbon activated filter that can be restored in an oven. Large glass top suited for placing dishes to serve customers. Electrical plugs protected by covering plates. Side supports each holding 2 each GN 1/9 (4-1/4" x 6-15/16") containers - 4 in total. Mounted on 4 swiveling wheels (two with brake). Rounded edges and smooth surfaces for easier cleaning. Cord and plug included.







#### APPROVAL:

#### **Main Features**

- Technological 3-stage filtering system composed of: a mechanical labyrinth filter for bigger particles of grease and steam, a mesh (metallic net) filter and carbon activated filters to absorb residual humidity and odors.
- Can accommodate up to three (3) Libero Line tabletop appliances.
- Mounted on 4 swiveling wheels.
- Push open <u>optional</u> neutral drawers for additional storage space.
- Integrated variable speed fan ventilation system with multistep filter.
- Heavy duty Stainless steel construction.
- Glass side splash guards and stainless steel front serving shelf.
- IP24 protected (Protected from touch by hands greater than 12 millimeters and protected from water spray in any direction).
- ETL safety approved, complies with UL 962 and CSA 22.2 listings.
- ETL sanitation approved, complies with NSF/ANSI 2 listing.

## **Included Accessories**

 4 of Stainless steel 1/9 size (6 7/8" x 4 1/4") PNC 329050 container (height = 2.5")

# **Optional Accessories**

<ul> <li>Stainless steel 1/9 size (6 7/8" x 4 1/4") container (height = 2.5")</li> </ul>	PNC 329050 □
• Stainless steel 1/9 size (6 7/8" x 4 1/4") container (height = 4")	PNC 329051 □
• Stainless steel 1/9 size (6 7/8" x 4 1/4") lid for containers	PNC 329052 □
<ul> <li>Tilting side shelf for Libero Point</li> </ul>	PNC 650005 🖵
<ul> <li>Set of 2 front panels (BLUE color) for Libero Point 3</li> </ul>	PNC 650007 □
EUTECTIC PLATE	PNC 650013 🖵
<ul> <li>Set of 2 front panels (RED color) for Libero Point 3</li> </ul>	PNC 650015 □
<ul> <li>Set of 2 front panels (GREEN color) for Libero Point 3</li> </ul>	PNC 650016 □
<ul> <li>Top neutral drawer for Libero point</li> </ul>	PNC 650030 🖵
• Top central neutral drawer for Libero point	PNC 650031 🖵
<ul> <li>Bottom neutral drawer for Libero point</li> </ul>	PNC 650033 🖵
• - NOT TRANSLATED -	PNC 653698 □
• - NOT TRANSLATED -	PNC 653699 □
• - NOT TRANSLATED -	PNC 653700 🖵
• - NOT TRANSLATED -	PNC 653701 🖵
• - NOT TRANSLATED -	PNC 653702 🖵

- NOT TRANSLATED -



# Libero Line Series Libero Point 3 freestanding self-ventilated downdraft cart

### **Electric**

Supply voltage:

**600064 (ELP3UX)** 208 V/3 ph/60 Hz

Amps: 0

**Total Watts:** 0.3 kW **Plug Type:** NEMA 15-50P

MCA: 34A Motor electrical power: 0,3 kW

## **Key Information:**

**External dimensions, Width:** 51 9/16" (1310 mm) **External dimensions, Depth:** 30 11/16" (780 mm) **External dimensions, Height:** 47 3/8" (1204 mm) Net weight: 287 lbs (130 kg) Shipping width: 36 5/8" (930 mm) 56 5/16" (1430 mm) Shipping depth: Shipping height: 55 1/2" (1410 mm) Shipping weight: 384 lbs (174 kg) Shipping volume: 66.21 ft<sup>3</sup> (1.88 m<sup>3</sup>)