EV9607-04 7 SO Softening Cartridge		
	7SO Replacement Cartridge: EV9707-04	 BENEFITS Softening cartridge reduces hardness in water that can cause minerals to build-up in coffee and espresso equipment Reduces minerals such as calcium and magnesium May be used on water having up to 30 grains hardness per gallon (500 mg/L) at flow rates of up to 1/2 gallon per minute Fits all existing Everpure heads. Recommended use as second cartridge in QC Twin Series configuration head (EV9272-24). Properly sized precoat filter cartridge should be installed before 7SO cartridge for best results Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination
 INSTALLATION TIPS Choose mounting location suitable to support the full weight of the system when operating Use 3/8" water line Install vertically with cartridge hanging down Allow 2-1/2" clearance below the cartridge for easy cartridge replacement Flush 7SO cartridge by running water through filter for five minutes at full flow 	OPERATION TIPS Change cartridges on a regular 6 month preventative maintenance program Change cartridges when hardness of treated water increases to more than 3 gpm Do not exceed recommended service flow rate Always flush the filter cartridge at time of installation and cartridge change	A P P L I C A T I O N / S I Z I N G For specialty coffee, espresso and ice tea applications Capacity: 2,000 grains softening Cartridge Grain Capacity divided by Grains Per Gallon In Influent Water = Total Product Water

7SO Softening Cartridge

18.75"

-,:=:=-7

S P E C I F I C A T I O N S

Overall Dimensions: 20.75"H x 3.25"Diameter

Service Flow Rate: Maximum 0.5 gpm (1.9 Lpm)

Pressure Requirements: 10 - 125 psi (0.7 – 8.6 bar), non-shock

Temperature: 35 - 100°F (2 - 38°C)

No electrical connection required

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

WARRANTY Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



EVERPURE, LLC 1040 Muirfield Drive Hanover Park, Illinois 60133 Toll Free (800) 323-7873 Tel (630) 307-3000 Fax (630) 307-3030 http://www.everpure.com In Europe: N.V. EVERPURE (EUROPE) S.A. Industriepark Wolfstee Toekomstlaan 30 B-2200 Herentals Belgium Tel 32 -14-283500 Fax 32-14-283505 In Japan: EVERPURE JAPAN LLC Hashimoto MN Bldg. 7F 3-25-1 Hashimoto Sagamihara-Shi Kanagawa 229-1103 Japan Tel 81-(0)42-775-3011 Fax 81-(0)42-775-3015

Everpure, LLC 1040 Muirfield Drive Hanover Park, IL 60133 Ph: 630-307-3000 Fax: 630-307-3030