

## S P E C I F I C A T I O N S

Overall Dimensions: 18.75"H x 3.25"Diameter

Service Flow Rate: Maximum 1.5 gpm (5.74 Lpm)

Rated Capacity: 30,000 gallons

Pressure Requirements: 10 - 125 psi (0.7 – 8.6 bar), non-shock


Temperature: 35 - 100°F (2 - 38°C)

No electrical connection required

Contents: Granular activated carbon

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.





## WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



Worldwide Headquarters: EVERPURE, LLC toqo Muirfield Drive Hanover Park, Illinois 60133 Toll Free (800) 323 - 7873 Tel (630) 307 - 3030 Fax (630) 307 - 3030 http://www.everpure.com In Europe: Pentair Water Belgium B.V./B.A. Industriepark Wolfstee Toekomstlaan 30 B-2200 Herentals BELGIUM TEL: +32.(0).14.283,500 FAX: +32.(0).14.283,505 In Japan: Hashimoto MN Bldg. 7F 3-25-1 Hashimoto Sagamihara-Shi Kanagawa 229-1103 JAPAN TEL: 81.(0)42.775.3011 FAX: 81.(0)42.775.3015

Everpure 1040 Muirfield Drive Hanover Park, IL 60133