



EV9627-13

MR-600 Replacement Cartridge

Mineral Reduction Cartridge



MR-600 Replacement Cartridge: EV9627-13

BENEFITS

- Improves equipment life and performance by removing at least 90%+ of all dissolved solids using Reverse Osmosis Separation Technology
- A reduction in Total Dissolved Solids (TDS) makes the water less likely to impart undesirable tastes in beverages, sauces, soups and other food products
- Especially useful on steamers, warmers, steam boilers and other evaporative equipment that are not emptied each day
- Heating surfaces maintain peak heat transfer efficiency, reducing cycle times and energy consumption
- Limits limescale build-up, which can cause excessive machine downtime and maintenance costs
- Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination

INSTALLATION TIPS

- Install vertically with cartridge hanging down
- Allow 2-1/2" clearance below the cartridge for easy cartridge replacement
- Use piping materials suitable for high-purity water after MRS System
- Refer to Installation, Operation & Maintenance manual for cartridge flushing and RO start-up

OPERATION TIPS

- Change MR Cartridge on a regular preventative maintenance program.
- Change MR Cartridge when output capacity diminishes by 15%, or when output pressure becomes too low.
- Always flush the MR cartridge at time of installation and cartridge change
- Proper pre-treatment is required to control MR Cartridge (membrane) scale formation and/or fouling.
 - Raw water hardness in excess of 7 grains per gallon should be softened to extend cartridge life
 - The raw water may contain chlorine or other oxidizers and the use of a carbon pre-filter is recommended.
- Contact EVERPURE Technical Service for pre-treatment recommendations

APPLICATION/SIZING

- Mineral Reduction Cartridge for High TDS Waters
- Capacity: 600 Gallons per Day nominal
- Ideal for:
 - Coffee/espresso machines, reconstitution, ice, flash steamers, conventional steamers, combiovens and multiple applications

MR-600 Replacement Cartridge

SPECIFICATIONS

Overall Dimensions:

25.00"H x 3.25"D

Daily Production Rate:

600 GPD (2,271 lpd) Nominal. Water pressure, feedwater quality and temperature will effect actual daily production rate

Service Flow Rate:

Dependant on water volume and pressure in storage tank(s), and line size(s) to equipment

Pressure Requirements:

40 - 100 psi (276 - 689 kPa), non-shock.

Inlet Temperature:

35 - 100°F (2 - 38°C)

Inlet TDS:

1,500 ppm max recommended

The contaminants or other substances removed or reduced by this system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.



WARRANTY

Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.

EVERPURE®

Worldwide Headquarters:

EVERPURE, LLC
1040 Muirfield Drive
Hanover Park, Illinois 60133
Toll Free (800) 323-7873
Tel (630) 307-3000
Fax (630) 307-3030
<http://www.everpure.com>

In Europe:

Pentair Water Belgium B.V./B.A.
Industriepark Wolfstee
Toekomstlaan 30
B- 2200 Herentals
BELGIUM
TEL: +32.(0).14.283.500
FAX: +32.(0).14.283.505

In Japan:

Hashimoto MN Bldg. 7F
3-25-1 Hashimoto Sagamihara-Shi
Kanagawa 229-1103
JAPAN
TEL: 81.(0)42.775.3011
FAX: 81.(0)42.775.3015

**Everpure
1040 Muirfield Drive
Hanover Park, IL 60133**