	0°, 0°, ×	C e
Adds sediment and carbon filtration ScaleStick®, which provides scale a		
		BENEFITS
	CWS-10 Carbon Block Filter Wrap: EV9799-06 SSW-10 Wrap ScaleStick: EV9799-04	 Features Hydroblend[™] compound, a unique blend that inhibits mineral scale deposits and provides corrosion protection in low flow water-fed equipment Patented design (patent no. 5,580,448) dispenses a controlled amount of Hydroblend[™] for long-term protection and provides greater effectivenes than standard phosphate treatments Unaffected by high temperatures, permitting a wide variety of applications Integral feed cartridge fits standard 10" housings Translucent cartridge allows simple visual monitoring of product usage and ensures against wasteful premature cartridge replacement Wrap ScaleStick[®] (SSW - 10) is specially designed to be used with a carbon block filter wrap (CWS - 10) to combine sediment filtration, chlorine reduction and scale control. The CWS - 10 is designed to fit over and around the Wrap ScaleStick[®] and is sold separately
N S T A L L A T I O N T I P S	OPERATION TIPS	A P P L I C A T I O N / S I Z I N G
Housing not included. Order Model A-10 Clear o" Housing (EV9100-01) separately for emperatures less than 125 F Make sure selected housing fits temperature/ oressure conditions Install vertically with black o-band seal up	Deliming of equipment prior to application is recommended, but not required Inspect ScaleStick [®] cartridges at least every 6 months Replace ScaleStick [®] before Hydroblend [™] compound is completely dissolved	nmended, but not required ect ScaleStick [®] cartridges at least every 6 ths ace ScaleStick [®] before Hydroblend [™] pound is completely dissolved
Vrap ScaleStick [®] cartridges are shorter than candard ScaleStick [™] cartridges and do not have ne o-band seal. They cannot be installed without ne special filter wraps. Standard ScaleStick [®] artridges cannot be installed into filter wraps	Pre-existing equipment scale may come loose and clog equipment. Remove any loose scale to assure satisfactory operation	

CWS-10 Carbon Filter Wrap

S P E C I F I C A T I O N S

Dimensions:

Filter Wrap: 7-11/16"H x 2-13/16" Diameter

Wrap ScaleStick SSW-10: 9-9/16" x 1-5/16" Diameter

Service Flow Rate: 0.1 - 6 gpm

Maximum Temperature: 150°F*

*If inlet feed water temperature is above 125°F a hot water housing must be used. Note: Filter Wraps are not to be used in hot water feed applications.

**The ScaleStick® trademark is used pursuant to an agreement between PWC Enterprises and Everpure, Inc. 2.813"

WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



Worldwide Headquarters: EVERPURE, LLC 1040 Muirfield Drive Hanover Park, Illinois 60133 Toll Free (800) 323-7873 Tel (630) 307-3030 http://www.everpure.com In Europe: Pentair Water Belgium B.V./B.A. Industriepark Wolfstee Toekomstlaan 30 B-2200 Herentals BELGIUM TEL: +32.(0).14.283,500 FAX: +32.(0).14.283,505 In Japan: Hashimoto MN Bldg. 7F 3-25-1 Hashimoto Sagamihara-Shi Kanagawa 229-1103 JAPAN TEL: 81.(0)42.775.3011 FAX: 81.(0)42.775.3015