

## **EBB23**





# **EBB Series**

#### **Refrigeration System**

- · Back mounted, self-contained and fully detachable Blizzard R290 condensing unit uses environmentally friendly, EPA-compliant R290 refrigerant with zero (0) Ozone Depletion Potential (ODP) and three (3) Global Warming Potential (GWP). Blizzard R290 is easily replaceable and requires no on-site brazing.
- · Electronically commutated (ECM) fan motors achieve rapid cooling with less energy consumption.
- · Full-length air duct ensures optimal cold air circulation.
- · Time-initiated and temperature-terminated auto defrost cycle for seamless operation.
- · Large capacity, corrosion-resistant condenser and evaporator coils.
- · Self-maintaining, energy-efficient condensate drain pan requires no external drains or electric heaters.
- · High performance, auto-reverse condenser fan motor supports compressor ventilation and condenser coil cleaning.
- · Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P.

### Cabinet Construction

Heavy duty stainless steel countertop with textured laminate, black vinyl exterior.

- · Galvanized steel interior walls and high quality stainless steel floor.
- ·13/4" thick high density polyurethane insulation.
- · Four pre-installed 5" swivel casters with locks on front set.
- · Built-in caster thread receptacles.

#### Lighting

· Shielded LED bar lighting with on/off switch provides bright, high color illumination at lower heat output.

#### Doors

- Textured laminate, black vinyl exterior with galvanized steel interior.
- ·13/4" thick high density polyurethane insulation.
- · Snap-in magnetic door gasket make cleaning and replacement an easy process.
- · High strength, recessed door handles.
- · Pre-installed door locks keep your items safe from theft.

### Shelving

- · Two epoxy coated, steel wire shelves per section.
- · Height adjustable stainless steel clips.

### **Temperature Control**

- · Multi-function digital controller with easy to read LED display.
- · Factory preset temperature, 35°F. Temperature setting range from 33°F to 54°F.
- · Audible overheat protection alarm for compressor and condenser coil.

#### Options

- · Additional shelving.
- $\cdot$  3" or 5" swivel casters with locks.
- · 3.5" 6" height-adjustable and interchangeable legs.



















Туре	Doors	Capacity Cu. Ft.	12 oz. Cans	12 oz. Bottles	Shelves	Refrigerant	НР	Power V-Hz-Ph	Amps	Crated Weight	Exterior Dimensions		
											L	D	H*
REF	1	8	220	125	2	R-290	1/5	115-60-1	2.5	167 lbs	23.5"	32"	39.375"

# **BACK BAR COOLER**



# **EBB23**

# **EBB Series**

### **DIMENSIONAL DATA**


	L	23.5 in.	
External Dims.	D	32 in.	
	H*	39.375 in.	
Crated Weight	167 lbs.		
Doors/Drawers/	1		
Max Weight Sup	-		


### **STORAGE DATA**

Net Capacity Cu. Ft. 🟲	8
Shelves	2
Barrels	-
20 oz. Bottles	-
12 oz. Bottles	125
12 oz. Cans	220
8" Mugs	-
# of Pans (Top)	-
# of Pans (Drawer)	-
Dividers	-
Trays	-

### **ELECTRICAL DATA**

Voltage	115-60-1
Full Load Amperage	2.5A
Feed Wires w/ Ground	3
Cord Length	9ft
NEMA Plug Type	(i) NEMA 5-15P





SIDE

19 3/4" 32" 53 3/4" TOP

## REFRIGERATION DATA

Compressor	Back
Refrigerant	R-290
Compressor HP	1/5
BTU/HR <sup>†</sup>	1655

### **KEY**

D L H FD SD GD	Lic Ho Fu Sc	oor d alf Door all Door olid Door ass Door	R REF F FRZ DUAL DR	Freezer Freezer		)
		Elevation	Right	Plan	3D	Back

	Elevation	Right	Plan	3D	Back
KCL					

### **ACCESSORIES & OPTIONS**

- Additional Shelving
- \_\_ AJL03-00
- CASA3-01
- Contact Everest Refrigeration for more information.
- Interchangeable Leg for Caster (Optional)
- 3" Overall Height Caster Assembly (2) Front (2) Rear