24" DIRECT DRAW KEG REFRIGERATORS

• EBDS2-24 • EBD2-24 • EBD3-24 • EBD4-24





EBD - Series

EBDS2-24



EBD2-24





EBD4-24

Cabinet Construction

Heavy duty stainless steel countertop with textured and laminated black vinyl exterior. Galvanized steel interior wall, and high quality stainless steel floor. 1 3/4" thick high density foamed-in-place polyurethane insulation. Built-in caster thread receptacles for all units.

Refrigeration System

- Side mounted condensing unit
- Oversized condenser and evaporator coils quickly achieve and maintain desired temperature
- Forced-air cooling with oversized evaporator fan motors providing balanced airflow throughout cabinet to ensure faster temperature drop
- Removable side panel and slide-out condensing unit for convenient repair and maintenance
- Environmentally friendly CFC free R-134A refrigerant
- Air defrost controlled by electrical timer
- Copper tube and aluminum fin evaporator with anti-corrosive coating
- Energy efficient condensate drain pan assembly heated by high side copper tube
- Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P

Doors

- · Textured and laminated black exterior with galvanized steel interior
- 1 3/4" thick high density foamed-in-place polyurethane insulation
- · One piece snap-in magnetic door gaskets for easy replacement
- · Heavy duty recessed door handles for a flat surface
- Door locks

Draft Arms

- NSF approved 3" diameter insulated stainless steel draft arm with air distributor
- Two draft arms

Lighting

• Shielded incandescent interior lighting with on/off switch

Temperature Control

- Factory preset temperature, 35°F
- Temperature setting range from 32°F to 42°F
- · Easy to set analog thermostat

Options

- 2 1/2" and 4" diameter casters (3 1/2" and 5" overall height)
- · Dual faucet towers


24" DIRECT DRAW KEG REFRIGERATORS





EBD – Series


• EBDS2-24 • EBD2-24 • EBD3-24 • EBD4-24

Dimensions









Model	Ref/ Fzr/ Dual	# of Doors	Capacity & Size of Barrels	Capacity (Cu.Ft.)	НР	Refrigerant	Power (V-Hz-Ph)	Amps	Crated Weight (LBS)	Exterior Dimensions (Inches)			* Height does not include towers
										L	D	н*	Ref = Refrigerator
EBDS2-24	Ref	2	(1) 1/2 (1) 1/4 - slim	13.95	1/4	R-134A	115-60-1	4.20	238	49	24 1/2	37	Fzr = Freezer Dual = Ref & Fzr Combo
EBD2-24	Ref	2	(2) 1/2	16.86	1/4	R-134A	115-60-1	4.20	254	57 3/4	24 1/2	37	
EBD3-24	Ref	2	(3) 1/2	20.41	1/4	R-134A	115-60-1	4.20	282	68	24 1/2	37	
EBD4-24	Ref	3	(4) 1/2	27.76	1/3	R-134A	115-60-1	4.50	331	89 1/4	24 1/2	37	

Disclaimer: Product dimensions are for general purposes and not absolute value. Slight variations may exist. If dimensions are critical, please contact Everest.

