## 24" BACK BAR & DIRECT DRAW KEG REFRIGERATORS

EBD - Series

• EBDS2-BBG-24 • EBD2-BBG-24 • EBD3-BBG-24



www.EVERESTref.com



EBDS2-BBG-24



EBD2-BBG-24



EBD3-BBG-24

### **Cabinet Construction**

Heavy duty stainless steel countertop, with textured and laminated black vinyl exterior. Galvanized steel interior wall and high quality stainless steel floor. 1 3/4" thick high density foamed-in-place polyurethane insulation. Built-in caster thread receptacles for all units.

## **Refrigeration System**

- Side mounted condensing unit
- Oversized condenser and evaporator coils quickly achieve and maintain desired temperature
- Forced-air cooling with oversized evaporator fan motors providing balanced airflow throughout cabinet to ensure faster temperature drop
- Removable side panel and slide-out condensing unit for convenient repair and maintenance
- Environmentally friendly CFC free R-134A refrigerant
- · Air defrost controlled by electrical timer
- Copper tube and aluminum fin evaporator with anti-corrosive coating
- Energy efficient condensate drain pan assembly heated by high side copper tube
- Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P

#### **Doors**

- · Textured and laminated black exterior with galvanized steel interior for solid doors, and black PVC frames with low emissivity double pane glass system for glass doors
- 1 3/4" thick high density foamed-in-place polyurethane insulation
- One piece snap-in magnetic door gaskets for easy replacement
- · Heavy duty recessed and die cast door handles
- Door locks

#### **Draft Arms**

• NSF approved 3" diameter insulated stainless steel draft arm with air distributor

#### Lighting

• Shielded vertical LED interior lighting with on/off switch for energy saving, less heat generation and enhanced illumination (available from 2015 models)

#### Shelving

- · Two epoxy coated wire shelves
- Stainless steel pilasters and shelf clips

#### **Temperature Control**

- Factory preset temperature, 35°F
- Temperature setting range from 32°F to 42°F
- · Easy to set analog thermostat

#### **Options**

- 2 1/2" and 4" diameter casters (3 1/2" and 5" overall height)
- · Dual faucet towers

## Project / Customer • Item No. Model No.

# 24" BACK BAR & DIRECT DRAW KEG REFRIGERATORS


**EBD** – Series


• EBDS2-BBG-24 • EBD2-BBG-24 • EBD3-BBG-24





www.EVERESTref.com

#### **Dimensions**









Model	Ref/ Fzr/ Dual			Capacity (Cu.Ft.)	НР	Refrigerant	# of Shelves	Capacity		D		Crated	Exterior Dimensions			* Height does not include
								12 oz. Cans	12 oz. Bottles	Power (V-Hz-Ph)	Amps	Weight (LBS)		(Inches)	н*	towers
								ouno	Dottioo			( -,	L	D.	- 11	Donth door not include
EBDS2-BBG-24	Ref	1(SD) 1(GD)	(1) 1/2	13.95	1/4	R-134A	2	175	126	115-60-1	4.20	243	49	24 1/2	37	Depth does not include protruding door handle
EBD2-BBG-24	Ref	1(SD) 1(GD)	(1) 1/2	16.86	1/4	R-134A	2	245	168	115-60-1	4.20	265	57 3/4	24 1/2	37	Ref = Refrigerator Fzr = Freezer Dual = Ref & Fzr Combo
EBD3-BBG-24	Ref	1(SD) 1(GD)	(1) 1/2 (1) 1/4-Slim	20.41	1/4	R-134A	2	315	210	115-60-1	4.20	353	68	24 1/2	37	SD=Solid Door GD=Glass Door

Disclaimer: Product dimensions are for general purposes and not absolute value. Slight variations may exist. If dimensions are critical, please contact Everest.