

## Water Specification

Water Connection Inlet 1/4" Male Flare Fitting	Minimum Flow Rate 1 1/2 gpm [5.7 lpm]	Water Pressure 20-75 psig [138-517 kPa]
---	--	--

## Electrical Configuration

Plastic Brew Basket Configuration Code	Stainless Steel Brew Basket Configuration Code	Heater Configuration	Voltage	Phase	Wires	KW	Electrical Connection	Max Amp Draw	Gallon [Liter] / Hour
E214154	E214154M	1 x 1.7 kW	100-120	1	2+G	1.3-1.8	NEMA 5-15P	12.3-14.7	4.4 [16.7] <sup>(1)</sup>
E214151	E214151M	1 x 2.3 kW	100-120	1	2+G	1.7-2.4	NEMA 5-20P	16.5-19.7	5.8 [22.0] <sup>(1)</sup>
<b>UNIVERSAL VOLTAGE OPTIONS</b>									
E214171	E214171M	1 x 1.5 kW	120	1	2+G	1.6	NEMA 5-15P	13.0	3.9 [14.8] <sup>(1)(3)</sup>
Optional <sup>(2)</sup>	Optional <sup>(2)</sup>	2 x 1.5 kW	120/208-240	1	3+G	3.1	L1 / L2 / N+G	13.0	5.8 [22.0] <sup>(1)(3)</sup>
E214172	E214172M	1 x 1.7 kW	120	1	2+G	1.8	NEMA 5-15P	14.7	4.4 [16.7] <sup>(1)(3)</sup>
Optional <sup>(2)</sup>	Optional <sup>(2)</sup>	2 x 1.7 kW	120/208-240	1	3+G	3.5	L1 / L2 / N+G	14.7	8.7 [33.0] <sup>(1)(3)</sup>
E214173	E214173M	1 x 2.3 kW	120	1	2+G	2.4	NEMA 5-20P	19.7	5.8 [22.0] <sup>(1)(3)</sup>
Optional <sup>(2)</sup>	Optional <sup>(2)</sup>	2 x 2.3 kW	120/208-240	1	3+G	4.7	L1 / L2 / N+G	19.7	11.0 [41.6] <sup>(1)(3)</sup>

(1) Based on standard factory settings: 5.5 minute brew time; 0% prewet; 200°F water. 1 gallon per batch.

(2) Sold with factory cord & plug for 120 Volt configuration. Optional user connection to a terminal block requiring L1, L2, N and ground to 120/208-240 VAC. No airport locator for this group. User selectable for optional, dual in-series heater configuration.

(3) 3 liters per batch.

## Measurements

Height 34 3/8" [87 cm]	Width 11 3/4" [29 cm]	Depth 20 3/8" [51 cm]	Empty Weight 29 lbs [13 kg]	Filled Weight 55 lbs [25 kg]	Combined Filled Weight 66 lbs [34 kg] <small>BREWER + 1 FILLED L3D-10 DISPENSER</small>	Hot Water Tank Cap. 3.3 gal [12 l]	Shipping Weight: 41 lbs [18 kg]	Shipping Dimensions: 16" x 23" x 29" [40 x 58 x 73 cm]
------------------------------	-----------------------------	-----------------------------	-----------------------------------	------------------------------------	---	--	---------------------------------------	--

## Cups per Hour\*

8oz.	184
12oz.	123
16oz.	92
20oz.	74

\* Approximate based on maximum power setting.

## Compatible Dispensers

**L3D-10**  
1.0 Gallon LUXUS®  
Thermal Dispenser

Product DIMS:  
Height: 21 1/2"  
Width: 8"  
Depth: 9"  
Weight:  
Empty: 8 lbs  
Filled: 15.9 lbs



**L3S-10**  
1.0 Gallon LUXUS®  
Thermal Server\*

Product DIMS:  
Height: 13 5/16"  
Width: 8"  
Depth: 10 1/4"  
Weight:  
Empty: 5.6 lbs  
Filled: 12.4 lbs



\* Must be used with S3S Serving Stations.

## Paper Coffee Filters

#F002  
13" x 5"  
Paper Coffee Filter



## Brew Baskets

#B014218BN2  
13" x 5"  
Plastic w/ Brown Insert



#B012218B1  
13" x 5"  
Stainless Steel



## Serving Stations

S3S-1 Single  
Serving Station



S3S-2 Twin  
Serving Station



S3S-3 Triple  
Serving Station

