

Water Specification

Water Connection Inlet 1/4" Male Flare Fitting	Minimum Flow Rate 1 1/2 gpm [5.7 lpm]	Water Pressure 20-75 psig [138-517 kPa]
---	--	--

Electrical Configuration

Plastic Brew Basket Configuration Code	Stainless Steel Brew Basket Configuration Code	Heater Configuration	Voltage	Phase	Wires	KW	Electrical Connection	Max Amp Draw	Gallon [Liter] / Hour
E214251	E214251M	2 x 3.0 kW	200-240	1	2+G	4.2-6.1	Hardwired	21.3-25.5	14.0 [53] ⁽¹⁾

(1) Based on standard factory settings: 5.5 minute brew time; 0% prewet; 200°F water. 1 gallon per batch.

Measurements

Height 34 3/8" [87 cm]	Width 19 3/4" [50 cm]	Depth 20 3/8" [51 cm]	Empty Weight 47 lbs [21 kg]	Filled Weight 92 lbs [41 kg]	Combined Filled Weight 114 lbs [51 kg] <small>BREWER + 2 FILLED L3D-10 DISPENSERS</small>	Hot Water Tank Cap. 5.8 gal [22 l]	Shipping Weight: 58 lb [26 kg]	Shipping Dimensions: 23" x 25" x 29" [58 x 63 x 73 cm]
------------------------------	-----------------------------	-----------------------------	-----------------------------------	------------------------------------	---	--	--------------------------------------	--

Cups per Hour*

8oz.	224
12oz.	149
16oz.	112
20oz.	90

* Approximate based on maximum power setting.

Compatible Dispensers

L3D-10
1.0 Gallon LUXUS®
Thermal Dispenser

Product DIMS:
Height: 21 1/2"
Width: 8"
Depth: 9"
Weight:
Empty: 8 lbs
Filled: 15.9 lbs



L3S-10
1.0 Gallon LUXUS®
Thermal Server*

Product DIMS:
Height: 13 5/16"
Width: 8"
Depth: 10 1/4"
Weight:
Empty: 5.6 lbs
Filled: 12.4 lbs



* Must be used with S3S Serving Stations.

Paper Coffee Filters

#F002
13" x 5"
Paper Coffee Filter



Brew Baskets

#B014218BN2
13" x 5"
Plastic w/ Brown Insert



#B012218B1
13" x 5"
Stainless Steel



Serving Stations

S3S-1 Single
Serving Station



S3S-2 Twin
Serving Station



S3S-3 Triple
Serving Station

