

**CBS-52H15 1.5 Gallon Coffee Brewer**

- Patented Gravity Dispense Tube System resists lime build up
- Holds a constant water temperature during 100% of brew cycle
- Maintains sprayover volume consistency
- Utilizes all solid state components



**CBS-52H15** with two 1.5 Gallon LUXUS® dispensers



Dual brew basket safety locks incorporated into start switch



Brews directly into FETCO® 1.5 gallon LUXUS® Thermal Dispensers

**LUXUS® TPD, LD, LS, L3D & L3S Dispensers**



## Water Specifications

Water Inlet <i>inch</i>	Flow Rate <i>gpm</i>	Water Pressure <i>psig</i>
3/8 Male Flare	1.25	20-75

## Measurements

Height <i>inch</i>	Width <i>inch</i>	Depth <i>inch</i>	Empty Weight <i>lbs</i>	Shipping Weight <i>lbs</i>
36	21	19 1/2	82	100

## Standard Electrical Configurations

Config. Code	Heater Config.	Voltage	Phase	Wires	KW	Max Amp Draw	Batches/Hour (1)	
							<i>cold water</i>	<i>hot water</i>
C52016	2x3.0 KW	120/208	1	3+G	4.6	22.4	7.7	17.2
		120/220			5.2	23.7	8.6	19.2
		120/240			6.1	25.8	10.2	22.0
C52026	2x4.0 KW	120/208	1	3+G	6.1	29.6	9.9	22.0
		120/220			6.8	31.3	11.5	22.0
		120/240			8.1	34.1	13.2	22.0
C52036(1)	3x3.0 KW	120/208	3	4+G	6.9	19.5	11.2	22.0
		120/220			7.7	20.6	12.9	22.0
		120/240			9.1	22.4	14.9	22.0
C52046(1)	3x4.0 KW	120/208	3	4+G	9.1	25.8	14.9	22.0
		120/220			10.3	27.3	17.3	22.0
		120/240			12.1	29.7	19.8	22.0
C52186(1)	3x4.0 KW	480	3	3+G	12.1	15.2	19.8	22.0
*C52076(1)	3x3.0 KW	220/380	3	4+G	7.7	11.9	14.9	22.0
*C52086(1)	3x4.0 KW	220/380	3	4+G	10.1	15.3	14.8	22.0
*C52096	2x3.0 KW	220/240	1	2+G	5.1/6.1	23.7/25.8	10.2	22.0
*C52106	2x4.0 KW	220/240	1	2+G	6.8/6.1	31.3/34.1	13.2	22.0
*C52116(1)	3x3.0 KW	220/240	3	3+G	7.7/9.1	20.6/22.5	14.9	22.0
*C52126(1)	3x4.0 KW	220/240	3	3+G	10.2/12.1	27.3/29.7	14.8	22.0

Specifications subject to change without notice

(1) Based on standard factory settings : 4.0 minute brew time, 0% prewet, 200°F water

\*EXPORT ONLY

