

CBS-62H Maritime IP44 Series

FETCO's IP44 Series is specifically designed for maritime use. Our IP44 certified compliant coffee brewing equipment is perfect for front-of-the-house and back-of-the-house applications on cruise ships.

- Delivers constant water temperature during 100% of brew cycle.
- Maintains sprayover volume consistency
- Gravity Dispense Tube System that resists lime buildup.

Use with FETCO's LUXUS® TPD-30 3.0 Gallon Dispenser. The LUXUS® TPD-30 dispenser provides hot beverage dispensing in volume. Once filled and capped, the stainless steel, fully thermo-insulated LUXUS® TPD-30 is specially designed to maintain the perfect serving temperature for hours.



CBS-62H with LUXUS® TPD-30



| Water Specifications | | | | | | | | |
|----------------------|---------------|---------------------|--|--|--|--|--|--|
| Water Inlet inch | Flow Rate gpm | Water Pressure psig | | | | | | |
| 3/8 Male Flare | 2.0 | 20-75 | | | | | | |

| Measurements | | | | | | | | |
|--------------|-----------------------|--------|------------------|---------------------|--|--|--|--|
| Height inch | Width inch Depth inch | | Empty Weight Ibs | Shipping Weight /bs | | | | |
| 40 | 35 1/2 | 22 3/8 | 195 | 197 | | | | |

| Standard Electrical Configurations | | | | | | | | | | | |
|------------------------------------|----------------|--------------------|-------|-------|--------------|--------------|--------------|--------------|--|--|--|
| Config. Code | Heater Config. | Voltage | Phase | Wires | KW | Max Amp Draw | Batches/Hour | | | | |
| | | | | | | | cold water | hot water | | | |
| C62186MIP | 6x4.0 KW | 440/480 | 3 | 3+G | 20.1 | 27.4 | 17.3 | 18.0 | | | |
| | | 440/480 | | | 24.1 | 29.7 | 18.0 | 18.0 | | | |
| C62196MIP | 3x4.0 KW | 440/480 440/480 | 3 | 3+G | 10.1 12.1 | 13.7 14.7 | 8.6 9.9 | 18.0 18.0 | | | |

Specifications subject to change without notice.







