APPLICATION: PRODUCT NAME: 4" C/C DECK FAUCET			
JOB NAME: QUANTITY: ITEM NO. MODEL: 07144 4" DECK LAVATORY WITH LEVER HANDLES OPTIONS OR MODIFICATIONS: SUPPLY LINES (24" OR 36") CIRCLE LENGTH VANDAL RESISTANT KIT HANDLES (CROSS OR WRIST) CIRCLE STYLE OTHER FEATURES CONTROL VALVE 4" DECK 5" SWIVELLING SEAT DISKS 5" STANLESS STEEL SEATS 7" STANLESS STEEL	APPLICATION:		PRODUCT NAME:
QUANTITY: TEM NO.			4" C/C DECK FAUCET
OPTIONS OR MODIFICATIONS: SUPPLY LINES (24" OR 36") CIRCLE LENGTH NANDAL RESISTANT KIT HANDLES (CROSS OR WRIST) CIRCLE STYLE OTHER FEATURES CONTROL VALVE "4" DECK "5" SWINLESS STEEL SPATS "5" STANLESS STEEL SPATS	JOB NAME:		
OPTIONS OR MODIFICATIONS: SUPPLY LINES (24" OR 36") CIRCLE LENGTH VANDAL RESISTANT KIT HANDLES (CROSS OR WRIST) CIRCLE STYLE OTHER CONTROL MALVE STANLESS STEEL SEAT SICKEWS STANLESS STEEL SEAT SCREWS STANLESS STEEL SEAT SCREWS	QUANTITY:	ITEM NO.	MODEL:
VANDAL RESISTANT KIT HANDLES (CROSS OR WRIST) CIRCLE STYLE OTHER			
[203.2mm] HANDLES (CROSS OR WRIST) CIRCLE STYLE OTHER O			☐ SUPPLY LINES (24" OR 36") CIRCLE LENGTH
FEATURES CONTROL VALVE '4" DECK 'SWIVELLING SEAT DISKS 'STAINLESS STEEL SEATS STAINLESS STEEL SEAT SCREWS 'STAINLESS STE	-	—8" -	
23-1/2" [88.90mm] CONTROL VALVE '4" DECK 'STAINLESS STEEL SATS 'STAINLESS STEEL SATS 'STAINLESS STEEL HANDLE SCREWS 'HOT & COUNTY OF THE WAY HAVE AND THE WAY HAVE		203.2mm]	
(88.90mm) - 4" DECK - SWIVELLING SEAT DISKS - STAINLESS STEEL SEATS - TEMP: 40" DECEMBER - TEMP: 40" DECEMBER - 15			FEATURES
**SWIVELING SEAT DISKS **STAILESS STEEL SEATS SCREWS **STAILESS STEEL SEATS STAILESS STEEL SEATS			
**STAINLESS STEEL HANDLE SCREWS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **SYSTEM LIMITS **TEMP-40°F MIN. TO 140°F MAX. **PRESSURE: 200 PSI MAX. STATIC **2.20 GPM @ 60 PSI **SHIPPING WEIGHT **4.25 LBS **ROUGH-IN: **ROUGH-IN: **TAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **HOT & COLD INDEX BUTTONS **STAINLESS STEEL HANDLE SCREWS **HOT & COLD INDEX BUTTONS **HOT & COLD			
STANLESS STEEL HANDLE SCREWS HOT & COLD INDEX BUTTONS **STANLESS STEEL HANDLE SCREWS** **HOT & COLD INDEX BUTTONS **SYSTEM LIMITS **TEMP-40°F MIN.** TO 140°F MAX. **PRESSURE: 200 PSI MAX. STATIC **2.20 SPM @ 60 PSI **SHIPPING WEIGHT **4.25 LBS **TANLESS STEEL HANDLE SCREWS** **HOT & COLD INDEX BUTTONS **STANLESS STEEL HANDLE SCREWS** **HOT & COLD INDEX BUTTONS **STANLESS STEEL HANDLE SCREWS** **HOT & COLD INDEX BUTTONS **STANLESS STEEL HANDLE SCREWS** **HOT & COLD INDEX BUTTONS **STANLESS STEEL HANDLE SCREWS** **HOT & COLD INDEX BUTTONS **STANLESS STEEL HANDLE SCREWS** **HOT & COLD INDEX BUTTONS **STANLESS STEEL HANDLE SCREWS** **HOT & COLD INDEX BUTTONS **STANLESS STEEL HANDLE SCREWS** **HOT & COLD INDEX BUTTONS **STANLESS STEEL HANDLE SCREWS** **HOT & COLD INDEX BUTTONS **STANLESS STEEL HANDLE SCREWS** **TEMP-40°F MIN.** **TEMP-40°F MIN.** **PRESSURE: 200 PSI MAX. STATIC **2.20 SPM @ 60 PSI **SHIPPING WEIGHT **4.25 LBS **STANLESS STEEL HANDLE SCREWS** **TEMP-40°F MIN.** **TEMP-40°F MIN	- The state of the	J Jours	
SYSTEM LIMITS 1/2" SLIP 101.6mm 101.			* STAINLESS STEEL HANDLE SCREWS
**TEMP; 40°F MINX. TO 140°F MAX. *PRESSURE: 200 PSI MAX. STATIC *2.20 GPM @ 60 PSI MAX. STATIC *2.20 GPM @ 60 PSI MAX. STATIC *4.25 LBS **SHIPPING WEIGHT *4.25 LBS ** **ROUGH-IN: **TEMP; 40°F MINX. TO 140°F MAX. **PRESSURE: 200 PSI MAX. STATIC **2.20 GPM @ 60 PSI MAX. STATIC **2.20 G			
# [101.6mm]			
ROUGH-IN: 101.6mm 30IN1 SHIPPING WEIGHT 4.25 LBS	-		
*4.25 LBS ROUGH-IN: Ø1-1/8" [28.58mm]		101.6mm] JOINT	
ROUGH-IN: Ø1-1/8" [28.58mm]		 n]	
Ø1-1/8" [28.58mm] ——————————————————————————————————	•	•	
Ø1-1/8" [28.58mm] ——————————————————————————————————			
[28.58mm] [101.6mm] [28.58mm]	ROUGH-IN:		
[28.58mm] [101.6mm] [28.58mm]			
[28.58mm] [101.6mm] [28.58mm]			
[101.6mm]			
FISHER			
	[101.01111]		

(F)

ANSI/A112.18.1M

FISHER MANUFACTURING COMPANY
TOLL FREE: 800-421-6162 - FAX: 800-832-8238
information@fisher-mfg.com - www.fisher-mfg.com