APPLICATION:		PRODUCT NAME: PRE-RINSE, SWIVEL STYLE, SINGLE DECK MOUNT
JOB NAME:		SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS
QUANTITY:	ITEM NO.	MODEL: 2011 ULTRA SPRAY VALVE NO WALL BRACKET 2011-WB ULTRA SPRAY VALVE W/ WALL BRACKET
11-1/2" [292mm] 3-3/4" [940mm] [51mm] [51mm] 5-1/4" [135mm] 1/2" SLIP JOINT KIT		OPTIONS OR MODIFICATIONS: SUPPLY LINES (24" OR 36") CIRCLE LENGTH ADD-ON FAUCET (6", 8", 10", 12", 14", 16") CIRCLE IN-LINE DUAL CHECK VALVE PIPE HOOK BRUSH HANDLES (CROSS OR WRIST) CIRCLE STYLE VANDAL RESISTANT KIT
		FEATURES
		* SINGLE DECK MOUNT * TEMPERATURE CONTROL VALVE WITH INTERNAL SPRING LOADED CHECK VALVES * STEM - LEFT HAND * HOT AND COLD INDEX BUTTONS * SWIVELLING SEAT DISK * STAINLESS STEEL SEAT * STAINLESS STEEL SEAT SCREW * STAINLESS STEEL HANDLE SCREW HOSE * 15-1/2" LENGTH * STAINLESS STEEL END FITTINGS * STAINLESS STEEL EXTERNAL JACKET * 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE * REPAIRABLE IN-FIELD WITH SIMPLE TOOLS ULTRA SPRAY VALVE * LOWEST ENERGY USER - 1.15 GPM @ 60 PSI * CLEANS FASTER - TEST PROVEN * ENGINEERED TO LAST - NO 'O' RINGS TO LEAK * INTERCHANGEABLE - FITS ALL BRANDS SYSTEM LIMITS * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE: 200 PSI MAX. STATIC SHIPPING WEIGHT * 12.0 LBS
ROUGH-IN:	Ø7/8" [22mm]	

FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238

information@fisher-mfg.com - www.fisher-mfg.com

ANSI/A112.18.1M

(1)