

APPLICATION:		PRODUCT NAME:	
		UTILITY SPRAY, DECK MOUNT	
JOB NAME:		<input type="checkbox"/> SPECIAL CONFIGURATION <input type="checkbox"/> CHECK BASE MODEL AND OPTIONS	
QUANTITY:	ITEM NO.	MODEL:	
		<input type="checkbox"/> 2170	
<p>ROUGH-IN:</p> <p>Ø1-1/4" [31.8mm]</p>		OPTIONS OR MODIFICATIONS:	
		<input type="checkbox"/> SUPPLY LINES (24" OR 36") CIRCLE LENGTH <input type="checkbox"/> ADD-ON FAUCET (6",8",10",12",14",16") CIRCLE LGTH <input type="checkbox"/> IN-LINE DUAL CHECK VALVE <input type="checkbox"/> VANDAL RESISTANT KIT <input type="checkbox"/> HANDLES (CROSS OR WRIST) CIRCLE STYLE <input type="checkbox"/> PIPE HOOK <input type="checkbox"/> BRUSH <input type="checkbox"/> OTHER _____	
		FEATURES:	
		CONTROL VALVE * SINGLE DECK DUAL CONTROL * HOT SIDE STEM - RIGHT HAND * COLD SIDE STEM - LEFT HAND * SWIVELLING SEAT DISKS * STAINLESS STEEL SEATS * STAINNESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS * FLEXIBLE INLET HOSES	
		HOSE * 60" LENGTH * STAINLESS STEEL END FITTINGS * STAINLESS STEEL EXTERNAL JACKET * 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE * REPAIRABLE IN FIELD WITH SIMPLE TOOLS	
		UTILITY SPRAY VALVE * NOZZLE THREADED INTO VALVE * 2.65 GPM AT 80 PSI * 45° ANGLED HEAD * SHOWER SPRAY PATTERN	
		SWIVEL ELBOW * 360° TURNING RADIUS	
		SYSTEM LIMITS * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE 200 PSI MAX. STATIC	
		SHIPPING WEIGHT * 9.0 LBS	
<p>FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com</p>			