APPLICATION:		PRODUCT NAME:
		WALL MOUNT POT FILLER HOSE STYLE
JOB NAME:		SPECIAL CONFIGURATION
		CHECK BASE MODEL AND OPTIONS
QUANTITY:	ITEM NO.	MODEL:
		2240
		OPTIONS OR MODIFICATIONS
		☐ SUPPLY LINES (24" OR 36") CIRCLE LENGTH
<del></del>	12" ————————————————————————————————————	☐ ADD-ON FAUCET (6", 8", 10", 12", 14", 16") CIRCLE
	77	□ BACKFLOW PREVENTER
	5"	□ PIPE HOOK
	[127mm]	□ NIPPLES
		□ ELBOWS
7-1/2"-8-1/2" (190.5mm-215.9mm)		□ VANDAL RESISTANT KIT
		☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE
		□ OTHER
/ <b>M</b>		FEATURES:
		CONTROL VALVE
		*ECCENTRICS ADJUST FROM 7-1/2" TO 8-1/2"
		*INTERNAL SPRING LOADED CHECK VALVES
		*SWIVELLING SEAT DISKS *HOT SIDE STEM - RIGHT HAND
Total Part of the second of th		*COLD SIDE STEM - LEFT HAND
		*STAINLESS STEEL SEATS
		*STAINLESS STEEL SEAT SCREWS *STAINLESS STEEL HANDLE SCREWS
		HOSE
		*60" LENGTH *STAINLESS STEEL END FITTINGS
		*STAINLESS STEEL EXTERNAL JACKET
		*USDA APPROVED FOODGRADE INTERNAL HOSE *REPAIRABLE IN FIELD WITH SIMPLE TOOLS
		REPAIRABLE IN FIELD WITH SIMPLE TOOLS
		POT FILLER VALVE
		*NON-SCRATCHING / MARRING TUBE  *5.0 GPM AT 80 PSI
		*AERATED STREAM
		OWN/EL EL BOW
		SWIVEL ELBOW *360° TURNING RADIUS
		*ATMOSPHERIC VACUUM BREAKER
		CVCTEM LIMITO
		SYSTEM LIMITS *TEMP: 40°F MIN. TO 140°F MAX.
		*PRESSURE 200 PSI MAX. STATIC
		SHIPPING WEIGHT
		*10.0 LBS
Ø7/8"		
[22.2mm]		
		HISHER