

**APPLICATION:**

**JOB NAME:**

**QUANTITY:** \_\_\_\_\_ **ITEM NO.:** \_\_\_\_\_

**PRODUCT NAME:**  
**PRE-RINSE SPRING STYLE**  
**8" C/C DECK MOUNT**

**SPECIAL CONFIGURATION**  
 **CHECK BASE MODEL AND OPTIONS**

**MODEL:**

**2310**      **ULTRA SPRAY VALVE, NO WALL BRACKET**

**2310-WB**    **ULTRA SPRAY VALVE, WALL BRACKET**

**OPTIONS OR MODIFICATIONS:**

**SUPPLY LINES (24" OR 36") CIRCLE LENGTH**

**ADD-ON FAUCET (6", 8", 10", 12", 14", 16") CIRCLE**

**IN-LINE DUAL CHECK VALVE**

**BRUSH**

**VANDAL RESISTANT KIT**

**HANDLES (CROSS OR WRIST) CIRCLE STYLE**

**OTHER** \_\_\_\_\_

**FEATURES**

**CONTROL VALVE**

- \* 8" C/C DECK MOUNT
- \* INTERNAL SPRING LOADED CHECK VALVES
- \* SWIVELLING SEAT DISKS
- \* HOT SIDE STEM - RIGHT HAND
- \* COLD SIDE STEM - LEFT HAND
- \* STAINLESS STEEL SEATS
- \* STAINLESS STEEL SEAT SCREWS
- \* STAINLESS STEEL HANDLE SCREWS
- \* 1/2" SLIP JOINT KIT

**HOSE**

- \* 36" LENGTH
- \* STAINLESS STEEL END FITTINGS
- \* STAINLESS STEEL EXTERNAL JACKET
- \* 3 PLY FIBER REINFORCED INTERNAL RUBBER HOSE
- \* REPAIRABLE IN FIELD WITH SIMPLE TOOLS

**ULTRA SPRAY VALVE**

- \* LOWEST ENERGY USER - 1.15 GPM @ 60 PSI
- \* CLEANS FASTER - TEST PROVEN
- \* ENGINEERED TO LAST - NO 'O' RINGS TO LEAK
- \* INTERCHANGEABLE - FITS ALL BRANDS

**WALL BRACKET**

- \* ADJUSTS FROM 2" TO 12"

**SYSTEM LIMITS**

- \* TEMP: 40°F MIN. TO 140°F MAX.
- \* PRESSURE: 200 PSI MAX. STATIC

**SHIPPING WEIGHT**

- \* 12.0 LBS

