APPLICATION:	
JOB NAME:	
QUANTITY:	ITEM NO.
38" [965.2mm] "A" [81.0mm]	12" [304.8mm] 0.219" 2 3/8" [60.9mm]

ROUGH-IN	MODEL	DIM "A"	DIM "B"	DIM "C"
1/2" NPT \[MALE*	27642	8-3/4" [221.3mm]	12-3/8" [313.3mm]	6" [152.4mm]
	27650	9" [227.6mm]	12-7/8" [326.0mm]	8" [203.2mm]
	27669	9-5/8" [243.5mm]	13-3/8" [340.3mm]	10" [254.0mm]
	27677	10-1/4" [259.4mm]	13-7/8" [351.4mm]	12" [304.8mm]
	27685	10 - 5/8" [275.0mm]	14-3/4" [373.7mm]	14" [355.6mm]
	37693	11-1/2" [292.1mm]	15-3/8" [389.5mm]	16" [406.4mm]

PRODUCT NAME:

PRE-RINSE SPRING SINGLE BACKSPLASH
WITH WALL BRACKET & ADD-ON FAUCET

SPECIAL CONFIGURATION

CHECK BASE MODEL AND OPTIONS

SPEC. PRHB-SPA-SBS

MODEL:

□ 27642 WITH 6" SWING SPOUT□ 27650 WITH 8" SWING SPOUT□ 27669 WITH 10" SWING SPOUT

☐ 27677 WITH 12" SWING SPOUT ☐ 27685 WITH 14" SWING SPOUT

☐ 27693 WITH 16" SWING SPOUT

OPTIONS OR MODIFICATIONS:

☐ SUPPLY LINES (24" OR 36") CIRCLE LENGTH
☐ ADD-ON FAUCET (6", 8", 10", 12", 14", 16") CIRCLE

☐ IN-LINE DUAL CHECK VALVE

□ BRUSH

□ VANDAL RESISTANT KIT

☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE

OTHER

FEATURES:

MAIN CONTROL VALVE

* SINGLE BACKSPLASH MOUNT

* INTERNAL SPRING LOADED CHECK VALVES

* SWIVELLING SEAT DISKS

* STEM - RIGHT HAND SWIVEL

* HOT AND COLD INDEX BUTTONS INCLUDED

* STAINLESS STEEL SEATS, SEAT SCREWS AND HANDLE SCREWS

ADD-ON CONTROL VALVE

* STEM - RIGHT HAND SWIVEL

* HOT INDEX BUTTON

* SWIVELLING SEAT DISKS

* STAINLESS STEEL SEATS, SEAT SCREWS AND HANDLE SCREWS.

HOSE

* 36" LENGTH

* STAINLESS STEEL END FITTINGS

* STAINLESS STEEL EXTERNAL JACKET

* 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE

* REPAIRABLE IN FIELD WITH SIMPLE TOOLS

ULTRA SPRAY VALVE

* LOWEST ENERGY USER - 1.15 GPM @ 60 PSI

* CLEANS FASTER - TEST PROVEN

* ENGINEERED TO LAST - NO 'O' RINGS TO LEAK

* INTERCHANGEABLE - FITS ALL BRANDS

WALL BRACKET

* ADJUSTS FROM 2" TO 12"

SYSTEM LIMITS

- * TEMP: 40°F MIN. TO 140°F MAX. STATIC
- * PRESSURE 200 PSI MAX. STATIC
- * SHIPPING WEIGHT: 12.0 LBS



TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com

2-3/8"-

[60.3mm]