APPLICATION:		PRODUCT NAME:	<u>SP</u>
		REEL RINSE UNDER COUNTER MOUNT	SPEC. 2984 REV. C
JOB NAME:		SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS	
QUANTITY:	ITEM NO.	MODEL:	— ് ი
70-5/8" [270.2mm] [24-1/4" [57.2mm]	ADAPTER X 1/2" FEMALE 10-1/2" [266.7mm] 10" [254.0mm] 4" [101.6mm]	□ 2984 WITH 12' HOSE OPTIONS OR MODIFICATIONS: □ BRUSH □ OTHER □ TEATURES: REEL * SELF LOCKING * EXPOSED HOSE * 12' LENGTH REEL HOSE * 19' LENGTH INLET HOSE * 3-PLY FIBER REINFORCED RUBBER HOSE * ADJUSTABLE BALL STOP STANDARD SPRAY VALVE * NOZZLE THREADED INTO VALVE * 2.65 GPM AT 80 PSI * SHOWER SPRAY PATTERN SYSTEM LIMITS * TEMP: 40'F MIN. TO 140'F MAX. * PRESSURE 200 PSI MAX. STATIC SHIPPING WEIGHT * 13.0 LBS	
Į2	03.2mmj	- ISHER	

(F) ANSI/A112.18.1M

FISHER MANUFACTURING COMPANY
TOLL FREE: 800-421-6162 - FAX: 800-832-8238
information@fisher-mfg.com - www.fisher-mfg.com