
APPLICATION:		PF
JOB NAME:		
QUANTITY:	ITEM NO.	М
"A" —		
		OF
	"C"	
	"B"	
8" [203.2mm]		FE
		*
4 2"		
2" [50.80r	nm]	

MODEL	DIM "A"	DIM "B"	DIM "C"
4510	6"	22-5/8"	26-1/4"
	[152.4mm]	[574.7mm]	[666.8mm]
4511	8"	22-7/8"	26-3/4"
	[203.2mm]	[581.0mm]	[679.4mm]
4512	10"	23-1/2"	27-1/4"
	[254.0mm]	[596.9mm]	[692.2mm]
4513	12"	24-1/8"	27-11/16"
	[304.8mm]	[612.8mm]	[703.3mm]
4514	14"	24-13/16"	28-5/8"
	[355.6mm]	[630.2mm]	[727.1mm]
2151	16"	25-7/16"	29-1/4"
	[406.4mm]	[646.1mm]	[743.0mm]

[101.6mm]



(1)

ANSI/A112.18.1M

PRODUCT NAME:

4" C/C DECK KETTLE FILLER

SPEC. 4510 REV.A

SPECIAL CONFIGURATION
CHECK BASE MODEL AND OPTIONS

MODEL:

☐ 4510 W/6" SWING SPOUT

☐ 4511 W/8" SWING SPOUT

□ 4512 W/10" SWING SPOUT

☐ 4513 W/12" SWING SPOUT

→ 4514 W/14 SWING SPOUT

¬ 2151 W/16" SWING SPOUT

OPTIONS OR MODIFICATIONS:

☐ SUPPLY LINES (24" OR 36") CIRCLE LENGTH

□ NIPPLES

☐ ELBOWS

☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE

□ VANDAL RESISTANT KIT

□ OTHER

FEATURES

* 4" DECK

* SWIVELLING SEAT DISKS

* HOT SIDE STEM - RIGHT HAND, COLD - LEFT HAND

* STAINLESS STEEL SEATS

* STAINLESS STEEL SEAT SCREWS

* STAINLESS STEEL HANDLE SCREWS

SYSTEM LIMITS

* TEMP: 40°F MIN. TO 140°F MAX.

* PRESSURE 200 PSI MAX. STATIC

* 2.20 GPM @ 60 PSI

SHIPPING WEIGHT

* 6.5 LBS



TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com