


SINGLE DECK DUAL CONTROL FAUCET W/ LEVER HANDLES




SINGLE DECK DUAL CONTROL FAUCET W/ WRIST HANDLES



FOOTPRINT:



ROUGH-IN:



ANSI/A112.18.1-2005

PRODUCT NAME: STAINLESS STEEL SINGLE DECK DUAL CONTROL FAUCET

☐ 52760 W/ 6" SWING SPOUT W/ LEVER HANDLES
│ □ 52779 W/ 8" SWING SPOUT W/ LEVER HANDLES
☐ 52787 W/ 10" SWING SPOUT W/ LEVER HANDLE
☐ 52795 W/ 12" SWING SPOUT W/ LEVER HANDLE
☐ 52809 W/ 14" SWING SPOUT W/ LEVER HANDLE
☐ 52817 W/ 16" SWING SPOUT W/ LEVER HANDLE
☐ 57266 W/ 6" SWING SPOUT W/ WRIST HANDLES
☐ 57274 W/ 8" SWING SPOUT W/ WRIST HANDLES
☐ 57282 W/ 10" SWING SPOUT W/ WRIST HANDLE
☐ 57290 W/ 12" SWING SPOUT W/ WRIST HANDLE
☐ 57304 W/ 14" SWING SPOUT W/ WRIST HANDLE
☐ 57312 W/ 16" SWING SPOUT W/ WRIST HANDLE

FEATURES

CONTROL VALVE

- * SINGLE DECK DUAL CONTROL
- * STAINLESS STEEL CONSTRUCTION
- * SWIVELLING SEAT DISKS
- * HOT SIDE STEM RIGHT HAND
- * COLD SIDE STEM LEFT HAND
- * LEVER HANDLES OR WRIST HANDLES
- * STAINLESS STEEL BRAIDED HOSE

SYSTEM LIMITS

- * TEMP: 40°F MIN. TO 140°F MAX. STATIC
- * PRESSURE 200 PSI MAX.
- * 2.20 GPM AT 80 PSI

SHIPPING WEIGHT

- * 4.75 LBS
- * NSF 61-9 APPROVED & LISTED www.truesdail.com

MODELS	DIM "A"	DIM "B"	DIM "C"
52760	3"	6-5/8"	6"
57266	[76.2mm]	[168.3mm]	[152mm]
52779	3-1/4"	7-1/8"	8"
57274	[82.6mm]	[181.0mm]	[204mm]
52787	3-7/8"	7-5/8"	10"
57282	[98.4mm]	[193.7mm]	[254mm]
52795	4-1/2"	8-1/8"	12"
57290	[114.3mm]	[206.4mm]	[305mm]
52809	5-1/8"	9"	14"
57304	[130.2mm]	[228.6mm]	[356mm]
52817	5"	9-5/8"	16"
57312	[149.2mm]	[244.5mm]	[406mm]



TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com