


BACKSPLASH



EPAct 2005 Compliant



ANSI/A112.18.1M

PRODUCT NAME:

8" BACKSPLASH PRE-RINSE WITH ADD-ON & ELBOWS

12" SWING SPOUT W/ LEVER HANDLES

SPEC. 55425

MODEL:

□ 55468

- $\ \square$ 55425 6" SWING SPOUT W/ LEVER HANDLES
- ☐ 55433 8" SWING SPOUT W/ LEVER HANDLES
- ☐ 55441 10" SWING SPOUT W/ LEVER HANDLES
- ☐ 55476 14" SWING SPOUT W/ LEVER HANDLES
- ☐ 55484 16" SWING SPOUT W/ LEVER HANDLES
- FEATURES:

CONTROL VALVE

- * 8" C/C BACKSPLASH MOUNT
- * CONCENTRICS
- * INTERNAL SPRING LOADED CHECK VALVES
- * SWIVELLING SEAT DISKS
- * HOT SIDE STEM RIGHT HAND
- * COLD SIDE STEM LEFT HAND
- * STAINLESS STEEL SEATS
- * STAINLESS STEEL SEAT SCREWS
- * STAINLESS STEEL HANDLE SCREWS
- * 1/2" CLOSE ELBOWS

ADD-ON CONTROL VALVE

- * STEM RIGHT HAND SWIVEL
- * HOT INDEX BUTTON
- * SWIVELLING SEAT DISKS
- * STAINLESS STEEL SEATS, SEAT SCREWS AND HANDLE SCREWS.

HOSE

- * 36" LENGTH
- * STAINLESS STEEL END FITTINGS
- * STAINLESS STEEL EXTERNAL JACKET
- * 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE
- * REPAIRABLE IN FIELD WITH SIMPLE TOOLS

ULTRA SPRAY VALVE

- * LOWEST ENERGY USER 1.15 GPM @ 60 PSI
- * CLEANS FASTER TEST PROVEN
- * ENGINEERED TO LAST NO 'O' RINGS TO LEAK
- * INTERCHANGEABLE FITS ALL BRANDS

WALL BRACKET

* ADJUSTS FROM 2" TO 12"

SYSTEM LIMITS

- * TEMP: 40°F MIN. TO 140°F MAX. STATIC
- * PRESSURE 200 PSI MAX. STATIC
- * SHIPPING WEIGHT: 15.0 LBS



TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com