APPLICATION: PRODUCT NAME: POT FILLER 3/4" SINGLE WALL WITH VACUUM BREAKER SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS MODEL: 5740 OPTIONS OR MODIFICATIONS: VANDAL RESISTANT KIT HANDLES (CROSS OR WRIST) CIRCLE STYLE OTHER FEATURES: CONTROL VALVE SNOVE WALL MOUNT SWIVEL OUTLET SWIVEL WISS STEEL SAT SCREWS STANLESS STEEL SAT SCREWS TAINLESS STEEL SAT SCREWS TAINLESS STEEL SAT SOREWS HOT & COLD INDEX BUTTONS INCLUDED HOSE TYP LG. HEAT MASTER FDA NITRILE/RAMID NSF-S1 (100 PSI WP-A TA 30°F) CONSTANT RENEWABLE END FITTINGS AND BUMPER INLET: 30° SWIVEL GOOSENECK NOW-MARRING GOOSENECK SON'S SWIVEL OF DOT WITH VINYL FINISH SON'S SWIVEL ATMOSPHERIC VACUUM BREAKER WALL HOOK INCLUDED ROUGH-IN: ROUGH-IN: ROUGH-IN: PROSUBE 200 PSI MAX. STATIC 29 GPM AT 80 PSI SHIPPING WEIGHT 11.0 LBS				
WALL HOOK	APPLICATION:			
QUANTITY: ITEM NO. MODEL: 5740 STAND OPTIONS STAND OPTIONS OR MODIFICATIONS: VANDAL RESISTANT KIT HANDLES (CROSS OR WRIST) CIRCLE STYLE OTHER OTHER SINGLE WALL MOUNT SWIVEL OUTLET SWIVEL NOT SEAT TORK STEEL SEAT SCREWS STAINLESS STEEL SEAT SCREWS HOT & COLD INDEX BUTTONS INCLUDED HOSE NSE-51 (100 PSI W.P. AT 300 PS) CONSTANT RENEWABLE END FITTINGS AND BUMPER NILET - 360 SWIVEL SPOUT WITH VINYL FINISH 360 SWIVEL ATMOSPHERIC VACUUM BREAKER WALL HOOK INCLUDED SYSTEM LIMITS STEMP: 40 PS MIN. TO 140 PS MAX. STATIC 29 POPM AT 80 PS MAX. STATIC 29 POPM AT 80 PS MAX. STATIC 29 PS MAY SEIGHT 11.0 LBS SHIPPING WEIGHT 11.0 LBS SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS MODEL: CHECK BASE MODEL AND OPTIONS OTHER HANDLES (CROSS OR WRIST) CIRCLE STYLE OTHER SWIVEL OUTLET SWIVEL OUTLET SWIVEL OUTLET SWIVEL OUTLET SWIVEL OUTLET SWIVEL OUTLET SWIVEL NOT SEAT STAND SWIVEL NOT SEAT SEAT SEAT SEAT SEAT SEAT SEAT SEA				
QUANTITY: TEM NO. MODEL: 5740 OPTIONS OR MODIFICATIONS: VANDAL RESISTANT KIT HANDLES (CROSS OR WRIST) CIRCLE STYLE OTHER FEATURES: CONTROL VALVE SINGLE WALL MOUNT SWIVELING SEAT DISKS STEME RICH HANDLE SCREWS STEME RICH HANDLE SCREWS STAINLESS STEEL SEAT SCREWS STAINLESS STEEL SEAT SCREWS STAINLESS STEEL SEAT SCREWS HOT & COLD INDEX BUTTONS INCLUDED HOSE 72° LG. HEAT MASTER FDA NITRILE/ARAMID NISF-51 (100 PSI W.P. AT 300°F) CONSTANT RENEWABLE END FITTINGS AND BUMPER INLET - 360° SWIVEL SPOUT WITH VINYL FINISH 360° SWIVEL ATMOSPHERIC VACUUM BREAKER WALL HOOK INCLUDED TZ" HOSE TEMP: 40°F MIN. TO 140°F MAX PRESSURE 200 PSI MAX. STATIC 29 GPM AT 80 PSI SI MAX. STATIC 29 GPM AT 80 PSI SI MAX. STATIC 29 GPM AT 80 PSI SI MAX. STATIC 29 GPM AT 80 PSI MAX. STATIC 29 GPM	JOB NAME:		SPECIAL CONFIGURATION	
OPTIONS OR MODIFICATIONS: VANDAL RESISTANT KIT HANDLES (CROSS OR WRIST) CIRCLE STYLE OTHER FEATURES: CONTROL VALVE SINGLE WALL MOUNT SWIVEL OUTLET SWIVELING SEAT DISKS STEM - RIGHT HAND STAINLESS STEEL SEATS STAINLESS STEEL SEATS STAINLESS STEEL SEAT SCREWS STAINLESS STEEL SEATS S	QUANTITY:	ITEM NO.		
WALL HOOK VANDAL RESISTANT KIT HANDLES (CROSS OR WRIST) CIRCLE STYLE OTHER TEATURES: CONTROL VALVE SINGLE WALL MOUNT SWIVEL OUTLET STAINLESS STEEL SEAT SCREWS SOS SWITCH SEAT SCREWS SOS SWITCH SEAT SCREWS SOS SWIT			□ 5740	
T2" HOSE 72" HOSE 72" HOSE 72" HOSE 72" HOSE 72" HOSE 72" HOSE 73" HOSE 74" HOSE 75" HOSE 76" FEMALE (133.4mm) 75" HOSE 76" FEMALE (133.4mm) 75" HOSE 76" FEMALE (133.4mm) 76" HOSE 77" HOSE 78" HOSE	14-3/8" [365.1mm]		□ VANDAL RESISTANT KIT	
FEATURES: CONTROL VALVE * SINGLE WALL MOUNT * SWIVEL OUTLE * SWIVEL OSEAT DISKS * STEM - RIGHT HAND * STAINLESS STEEL SEAT SCREWS * STAINLESS STEE			· · · · · · · · · · · · · · · · · · ·	
CONTROL VALVE SINGLE WALL MOUNT SWIVEL OUTLET SWIVELING SEAT DISKS STEM - RIGHT HAND STAINLESS STEEL SEATS STAINLESS STEEL SEATS STAINLESS STEEL SEAT SCREWS STAINLESS STEEL SEAT SCREWS TO STAINLESS STEEL HANDLE SCREWS TO STAINLESS STEEL SEAT SCREW				
72" HOSE 736" SWIVEL ATMOSPHERIC VACUUM BREAKER 736" SWIVEL HOSE 73			CONTROL VALVE * SINGLE WALL MOUNT * SWIVEL OUTLET * SWIVELING SEAT DISKS * STEM - RIGHT HAND * STAINLESS STEEL SEATS * STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS	
Ø1-1/4"	[127.0mm] [5] 72" HOSE 72" HOSE 3/4" NP	54.4mm] "m] -5-1/4"	* 72" LG. HEAT MASTER FDA NITRILE/ARAMID * NSF-51 (100 PSI W.P. AT 300°F) CONSTANT * RENEWABLE END FITTINGS AND BUMPER * INLET - 360° SWIVEL SPOUT WITH VINYL FINISH * 360° SWIVEL GOOSENECK * NON-MARRING GOOSENECK * 360° SWIVEL ATMOSPHERIC VACUUM BREAKER * WALL HOOK INCLUDED SYSTEM LIMITS * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE 200 PSI MAX. STATIC * 29 GPM AT 80 PSI SHIPPING WEIGHT	
Ø1-1/4" [31.8mm]	ROUGH-IN:			
	9	Ø1-1/4" [31.8mm]		