| APPLICATION:  |   | PRODUCT NAME: PRE-RINSE SPRING STYLE WALL MOUNT   |
|---|---|---|
| JOB NAME:   |   | ■ 80160 SPECIAL CONFIGURATION MODEL: (CHECK BASE MODEL AND OPTIONS)   |
| QUANTITY:   | ITEM NO.:                                     | ■ 2210-WB ULTRA SV WITH WALL BRACKET □ 2210 ULTRA SV, NO WALL BRACKET   |
|   |   | OPTIONS OR MODIFICATIONS:  SUPPLY LINES (24" OR 36") CIRCLE LENGTH  ADD-ON FAUCET (6",8",10",12",14",16") CIRCLE LGTH  IN-LINE DUAL CHECK VALVE  BRUSH  NIPPLES  ELBOWS  VANDAL RESISTANT KIT  HANDLES (CROSS OR WRIST) CIRCLE STYLE  OTHER                                   |
| 38"<br>[965.2mm]  | mm]   | FEATURES:   |
|   |   | CONTROL VALVE  * ECCENTRICS ADJUST FROM 7-1/2" TO 8-1/2"  * INTERNAL SPRING LOADED CHECK VALVES  * SWIVELLING SEAT DISKS  * HOT SIDE STEM - RIGHT HAND  * COLD SIDE STEM - LEFT HAND  * STAINLESS STEEL SEATS  * STAINLESS STEEL SEAT SCREWS  * STAINLESS STEEL HANDLE SCREWS |
| 12"—<br>[304.8mm  |   | HOSE  * 36" LENGTH  * STAINLESS STEEL END FITTINGS  * STAINLESS STEEL EXTERNAL JACKET  * 3-PLY FIBER REINFORCED INTERNL RUBBER HOSE  * REPAIRABLE IN FIELD WITH SIMPLE TOOLS  |
| 7-1/2"-8-1/2"-<br>[190.5mm]-[215.9mm]   |   | ULTRA SPRAY VALVE  * 1.6 GPM @ 80 PSI ENERGY EFFICIENT NOZZLE  * BRONZE HANDLE - NOT PLASTIC - MEANS FULL "ON"  * FITS ALL BRANDS   |
| ROUGH-IN: 2-1/4" (MAX)  |   | WALL BRACKET * ADJUSTS FROM 2" TO 12"   |
| [57.2Hill]<br>3"<br>[76.2mm]  | [108.0mm] 1/2" NPT FEMALE 1/2" SLIP JOINT KIT | SYSTEM LIMITS  * TEMP: 40°F MIN. TO 140°F MAX. STATIC  * PRESSURE 200 PSI MAX. STATIC  * SHIPPING WEIGHT: 12.0 LBS  |
| 7-1/2"-8-1/2"<br>1/2" NPT X 1-3/4" [190.5mm]-[215.9mm] NIPPLES Ø7/8" [22.2mm] |   | FISHER MANUFACTURING COMPANY  |
| <b>®</b> ANSI/A112.18.1M  |   | TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com   |