APPLICATION:	PRODUCT NAME: POT FILLER HOSE STYLE 8" C/C ADJUSTABLE WALL MOUNT
JOB NAME:	■ 83097 SPECIAL CONFIGURATION
QUANTITY: ITEM NO.:	(CHECK BASE MODEL AND OPTIONS)
112	■ 2250
BACK FLOW PREVENTOR————————————————————————————————————	OPTIONS OR MODIFICATIONS:
15 7/8" / 7 1/8"	SUPPLY LINES (24" OR 36") CIRCLE LENGTH
[403.4mm] [179.8mm]	□ ADD-ON FAUCET (6",8",10",12",14",16") CIRCLE LGTH ■ BACKFLOW PREVENTER
	□ PIPE HOOK
	■ NIPPLES
4" -3-1/8"	= ELBOWS
□ 4" □ 3-1/8" □ 101.8mm □ [80.5mm]	■ VANDAL RESISTANT KIT
-7-3/4"-8-1/4"-	■ HANDLES (CROSS OR WRIST) CIRCLE STYLE
[196.9mm-209.6mm]	OTHER
	FEATURES:
	CONTROL VALVE
60" LENGTH	* 8" C/C ADJUSTABLE WALL MOUNT
FOODGRADE HOSE	* ECCENTRICS ADJUST FROM 7-3/4" TO 8-1/4" * INTERNAL SPRING LOADED CHECK VALVES
	* SWIVELING SEAT DISKS
	* HOT SIDE STEM - RIGHT HAND * COLD SIDE STEM - LEFT HAND
	* STAINLESS STEEL SEATS
	* STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS
FOODGRADE HOSE	
	HOSE * 60" LENGTH
	* STAINLESS STEEL END FITTINGS
	* STAINLESS STEEL EXTERNAL JACKET * BRAIDED USDA APPROVED FOODGRADE
ROUGH-IN:	INTERNAL HOSE
	POT FILLER VALVE
<u>√</u> 1/2" NPT	* NON SCRATCHING/ MARRING TUBE
FEMALE	* 5.00 GPM AT 80 PSI * AERATED STREAM
WASHER & LOCKNUT	ALIVATED STREAM
LOCKNOT	SWIVEL ELBOW * 360° TURNING RADIUS
7-5/4-5-1/4	SYSTEM LIMITS * TEMP: 40°F MIN. TO 140°F MAX.
[196.9mm]-[209.6mm]	* PRESSURE 200 PSI MAX. STATIC
1/2" NPT MALE	SHIPPING WEIGHT
	* 9.0 LBS
Ø7/8"_/ [22.2mm]	
1/2" NPT / FEMALE ELBOWS	FISHER

(1)

ANSI/A112.18.1M, ANSI/NSF 61.9

FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com