APPLICATION:		PRODUCT NAME:
		PRE-RINSE SPRING STYLE WITH REMOTE CONTROL VALVE AND WALL BRACKET
JOB NAME:		SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS
QUANTITY:	ITEM NO.	MODEL:
		■ 96962 W/ 6" SWING SPOUT
	38" 5.2mm] WALL BRACKET [304.8mm] 12" [304.8mm]	OPTIONS OR MODIFICATIONS: SUPPLY LINES (24" OR 36") CIRCLE LENGTH ADD-ON FAUCET (6", 8", 10", 12", 14", 16") CIRCLE BACKFLOW PREVENTER BRUSH VANDAL RESISTANT KIT HANDLES (CROSS OR WRIST) CIRCLE STYLE OTHER FEATURES CONTROL VALVE * 4" C/C REMOTE CONTROL * INTERNAL SPRING LOADED CHECK VALVES * SWIVELLING SEAT DISKS * HOT SIDE STEM - RIGHT HAND * COLD SIDE STEM - LEFT HAND * STAINLESS STEEL SEATS * STAINLESS STEEL SEATS * STAINLESS STEEL HANDLE SCREWS * 1/2" SLIP JOINT HOSE * 36" LENGTH * STAINLESS STEEL END FITTINGS * STAINLESS STEEL END FITTINGS * STAINLESS STEEL ENTERNAL JACKET * 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE SPRAY VALVE * SOLID BRASS SHOWER HEAD - NO O-RINGS TO LEAK * BRONZE HANDLE - NOT PLASTIC - MEANS FULL "ON" * FITS ALL BRANDS * 2.65 GPM AT 80 PSI WALL BRACKET
FOOTPRINT:		*ADJUSTABLE FROM 2" TO 12"
17/8" [47.6mm]	Ø1-7/8" [47.6mm]	SYSTEM LIMITS * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE: 200 PSI MAX. STATIC SHIPPING WEIGHT * 12.0 LBS
ROUGH-IN		
	Ø7/8" [22.2mm] [22.2mm]	FISHER
(F) ANSI/A112.18.1M		FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com