APPLICATION: PRODUCT NAME: PRE-RINSE SPRG SINGLE DECK DUAL CTI WITH WALL BRACKET & ADD-ON FAUCET 99899 JOB NAME: SPECIAL CONFIGURATION MODEL: QUANTITY: ITEM NO.: **34169** WITH 6" SWING SPOUT 34177 WITH 8" SWING SPOUT П 34185 WITH 10" SWING SPOUT 34193 WITH 12" SWING SPOUT 12" STAINLESS 34207 WITH 14" SWING SPOUT STEEL BRAIDED □ 34215 WITH 16" SWING SPOUT SUPPLY LINES OPTIONS OR MODIFICATIONS: & MOUNTING KIT □ SUPPLY LINES (24" OR 36") CIRCLE LENGTH BACKFLOW PREVENTER □ BRUSH □ VANDAL RESISTANT KIT □ HANDLES (CROSS OR WRIST) CIRCLE STYLE □ OTHER **FEATURES:** MAIN CONTROL VALVE * SINGLE DECK, DUAL CONTROL * INTERNAL SPRING LOADED CHECK VALVES SWIVELING SEAT DISKS [965.2mm] HOT SIDE STEM - RIGHT HAND CHECK COLD SIDE STEM - LEFT HAND CHECK STAINLESS STEEL SEATS, SEAT SCREWS AND HANDLE SCREWS **BACKFLOW** 1/2"F NPT ADD-ON CONTROL VALVE **PREVENTER** INLETS STEM - RIGHT HAND SWIVEL * HOT INDEX BUTTON * SWIVELING SEAT DISKS STAINLESS STEEL SEATS, SEAT SCREWS AND HANDLE SCREWS HOSE 12" 36" LENGTH [304.8mm] * STAINLESS STEEL END FITTINGS * STAINLESS STEEL EXTERNAL JACKET "Ė' 9-3/4" * 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE [247.7mm] "A" [177.8mm] BACKFLOW PREVENTER ATMOSPHERIC VENT FOR IN-LINE CONTINUOUS PRESSURE [50.8mm] **APPLICATIONS** DOUBLE CHECK DESIGN FOOTPRINT: 1-3/4" **ULTRA SPRAY VALVE** [42.9mm] 1.6 GPM @ 80 PSI ENERGY EFFICIENT NOZZLE 2-5/8" **BRONZE HANDLE - NOT PLASTIC - MEANS** [65.5mm] **FULL "ON"** * FITS ALL BRANDS DIM "B" **ROUGH-IN** MODEL DIM "A" DIM "C" 12**-**3/8" [313.3mm] 8-3/4" WALL BRACKET 34169 [221.3mm] [152.4mm] * ADJUSTS FROM 2" TO 12" 12-7/8" 34177 [326.0mm] SYSTEM LIMITS [227.6mm] [203.2mm] □ 1-1/4" TEMP: 40°F MIN. TO 140°F MAX. STATIC [31.8mm] 9-5/8" 13-3/8" 10" * PRESSURE 200 PSI MAX. STATIC 34185 [243.5mm] [340.3mm] [254.0mm] * SHIPPING WEIGHT: 16.0 LBS 12" 10-1/4" 13-7/8" 34193 [259.4mm] [351.4mm] [304.8mm] 10-7/8" 14-3/4" 14" 34207 [275.2mm] [355.6mm] [373.7mm] 15HEF 11-5/8" 15-3/8" 16" 34215 [406.4mm] [294 3mm] [389.5mm] FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238 B ANSI/A112.18.1M, ANSI/NSF 61.9 information@fisher-mfg.com - www.fisher-mfg.com