

Designer Series Electric Griddles

Item:	_
Quantity:	
Project:	
Approval:	
Date:	

Models:			
☐ ED-15G	ED-24G	☐ ED-36G	
☐ EDU-15G	☐ EDU-24G	☐ EDU-36G	



Model ED-24G

Standard Features:

- · Stainless steel front and sides
- Easy clean design with recessed protected controls.
- · Heat-On indicator lamps
- Thermostat controlled one per foot of width
- Models with EDU prefix are "CE" approved
- 18" (457mm) deep cooking surface
- 4" (102mm) Stainless Steel legs.
- 1/2" (13mm) polished steel griddle with 2-5/8" (67mm) welded splash guard on sides and rear of plate

- Concealed grease drawer
- One-Year limited parts & labor warranty (USA & Canada only)

Optional Features:

- ☐ Stainless steel back and bottom
- Fully grooved griddle, add suffix U (i.e. GD-15GU) or grooved sections, add U1 for 12"(305mm) on left side and U2 for 24" (610mm) on left side

Note: Stands are available see form # CS24/CSD

Specifications:

Electric designer series griddles in three widths: models ED-15G, 15" (381mm) wide; ED-24G, 24" (610mm) wide and ED-36G, 36" (914mm) wide. Designed as free standing or to be banked with other ED series equipment. 24" (610mm) deep x 13-3/4" (349mm) high, easy clean design with stainless steel front and sides. Thermostat controlled, with improved insulation underneath the elements allowing for better heat efficiency. Concealed grease drawer behind lower hinged panel. Fully grooved or grooved section griddle available. Models with EDU prefix are "CE" Approved.












General Inquiries 1-905-624-0260 USA Sales, Parts and Service 1-800-424-2411 Canadian Sales 1-888-442-7526 Canada or USA Parts/Service 1-800-427-6668






	Total kW Load			Nominal Amperes Per Line								
	iotai kw Load				North America			Export				
Models	North Export		l	gle ase			Single Phase		Hi Line - 2 or -3 Phase			
	208V	240V	220V/ 380V	240V/ 415V	208V	240V	208V	240V	220V/ 380V	240V/ 415V	220V/ 380V	240V/ 415V
ED-15G, EDU-15G	3.4	3.4	3.4	3.4	17	14	N/A	N/A	16	14	N/A	N/A
ED-24G, EDU-24G	6.7	6.7	6.7	6.7	33	28	28	25	31	28	16	14
ED-36G, EDU-36G	10.1	10.1	10.1	10.1	49	42	28	25	46	42	16	14


NA -	Ove	rall Dimensior	ıs	Useable Cook	C F4	Shipping	
Model	Height Width		Depth	Width	Depth	Cu Ft	Wt. Lb/kg
ED-15G	13-3/4" (349mm)	15" (381mm)	24" (610mm)	14-5/8" (371mm)	18" (457mm)	6	90/41
ED-24G	13-3/4" (349mm)	24" (610mm)	24" (610mm)	23-5/8" (600mm)	18" (457mm)	8	135/61
ED-36G	13-3/4" (349mm)	36" (914mm)	24" (610mm)	35-5/8" (876mm)	18" (457mm)	11	175/80



Garland products are not approved or authorized for home or residential use, but are intended for commercial applications only. Garland will not provide service, warranty, maintenance or support of any kind other than in commercial applications.

Installation Clearances				
Side	Rear			
1" (25mm)	1.5" (38mm)			





Form# ED-15G, ED-24G, ED-36G (01/16/12)

