



# Induction Green Heat

## Garland Induction Fajita Skillet Warmer 3.5kW

Item: GI-SH/BA 3500FH

Article No.: 99600017

Quantity: \_\_\_\_\_

Project: \_\_\_\_\_

Approval: \_\_\_\_\_

Date: \_\_\_\_\_

Induction Green Heat  
Garland Induction Fajita Skillet Warmer 3.5kW

### Models:

GI-SH/BA 3500FH



### Induction Benefits:

- Energy Efficient
- Fast Heat
- Easy To Clean
- No Pan, No Heat.
- Cool Operations

### Standard Features

- Compact table top design with stainless steel body and high impact ceramic glass top
- "Flat Design", compact high performance electronics allow for low unit heights.
- Sloped front panel for easy cleaning and operation
- One rear discharge integral cooling fan keeps electronics cool; protective air deflectors prevent hot exhaust to be pulled back into the unit.
- Removable, reusable easily cleaned air intake filter.
- Induction technology transfers heat to pan instantly.
- Four position selector switch for precise operational settings: Off, Fajita (78 sec), Reheating (20 sec), and Desert (32 sec).
- Innovated technology for pan detection; RTCS is an internal control software development matching speed, capability and performance
  - R – Real Time
  - T – Temperature
  - C – Control
  - S – System
- Overheat sensor shuts unit off preventing pans cooking dry.
- 6' (1829mm) cord and plug supplied 208V 3.5kW

### Options & Accessories

- Extra replacement air intake filter stock SKU# 71000003 (available as a replacement part through your local authorized parts and service depot).

### Specifications:

Shall be a Garland Induction Skillet Warmer, Model GI-SH/BA 3500FH, with total kW rating of 3.5, Unit to be constructed of all stainless steel with ceramic glass top. Unit to have a control with four settings: Off, Fajita (78 sec), Reheating (20 sec), and Desert (32 sec). LED indicator to signal end of timed cycle, and automatic turn-off at the end of cycle to prevent overheating. Unit to come in 208V, Single Phase, 60Hz power with integral cord and plug supplied.

Note: The Garland Induction Fajita skillet warmer is designed only to heat empty, oval, cast-iron fajita pans. It cannot be used with general designed induction pans for sauté or any other application.



**Intertek**

North American models:  
ETL listed in compliance with  
UL 197, CSA C22.2 No.109, NSF-4  
Complies with FCC part 18, ICES-001

Garland Commercial Ranges Ltd.  
1177 Kamato Road,  
Mississauga, Ontario  
L4W 1X4 CANADA

General Inquiries 1-905-624-0260  
USA Sales, Parts and Service 1-800-424-2411  
Canadian Sales 1-888-442-7526  
Canada or USA Parts/Service 1-800-427-6668



3.35" (85mm) | 3" (75mm) | 8.65" (220mm)

AIR EXHAUST

CERAN PLATE

12.6" (320mm)

17.325" (440mm)

12.6" (320mm)

Garland/U.S. Range products are not approved or authorized for home or residential use, but are intended for commercial applications only. Garland / U.S. Range will not provide service, warranty, maintenance or support of any kind other than in commercial applications.

WALL

MIN. DISTANCE TO WALL = 1.6" (40mm)

AIR EXHAUST

CABLE

AIR SUPPLY

8.8" (224mm)

REMOVABLE GREASE FILTER

5.5" (140mm)

2.4" (61.5mm)

**Installation Notes:**

- Installation should be performed by qualified personnel only.
- The appliance must be placed on a level, stable, dry, and non-flammable surface.
- This unit is equipped with a removable grease filter that must be clean and dry during operation.
- The Skillet Warmer must not be placed next to other heat or steam sources (e.g. fryers, open top ranges, griddles, broilers, ovens and steam equipment). Heat and/or steam entering the Skillet Warmer's cooling intake could result in failure due to overheating.
- Isolate unit from heat, grease, and steam sources.
- The air intake, (located on the bottom front), and air outlet, (located at the rear), must not be obstructed. Obstruction of the cooling intake could result in failure due to overheating.
- Air exhaust may be extremely hot. Allow proper rear clearance to a surface that is resistant to heat damage.
- Ambient temperature for cooker should be no more than 110°F (40°C).
- Kitchen relative humidity 30 to 90%.
- Air intake filter must be cleaned weekly.

Plug Configurations		
Model	Electrical Characteristics	Plug
GI-SH/BA 3500FH	208V/60Hz/1Ø 240V/60Hz/1Ø	 NEMA 6-20P
	230V/50Hz/1Ø	 EU1-16P

Electrical Loading				
Model	Watts	208/60/1	240/60/1	230/50/1
GI-SH/BA 3500FH	3500	17 amp	14 amp	15 amp

Form# GI-SH/BA 3500FH (05/06/13)