

Project Name:

AIA#:_____ SIS#:____

Model #:____ Item #: ____

C-Series Compact Manual Slicer



C9 - 9" Diameter Knife Manual Slicer



Enhanced Cleanability and Sanitation Features Certified by NSF International - NSF/ANSI 8 - 2010 Standard

Quality Construction

- Anodized aluminum construction with seamless edges and radius corners
- Lightweight and compact Italian space-saving design
- Hard chromed, special alloy hollow ground knife
- Top mounted, all metal knife sharpener
- Removable, easy-to-clean chute, slice deflector, knife cover, and sharpener
- Metal bottom enclosure
- Moisture proof, easy-to-clean On/Off switch
- Sealed splash zones for added sanitation and protection of electronics

Standard Features

- 0 to 9/16" slice thickness
- 1/4 HP knife motor
- Motor overload protection with manual reset
- Oversized positive traction grooved belt drive
- Smooth stainless steel ball bearing chute slide
- Angled gravity feed chute
- Ergonomically designed, dual purpose handle
- Power indicator light

Quantity:

Compact Manual Slicer

WARRANTY:

One-year parts and labor

Optional Warranty Extension

Additional one-year warranty on parts and labor inside the continental U.S.



GLOBE FOOD EQUIPMENT COMPANY 2153 Dryden Rd., Dayton, OH 45439 Phone: 937-299-5493 Fax: 937-299-4147 800-347-5423 www.globeslicers.com

Approved By: _

Date:


Optional Accessories


□ SC-SMALL - Slicer Cover □ CB - Cleaning Brush



Compact Manual Slicer

C9





SPECIFICATIONS												
Mod	lel Auto o Manua		Volts	Amps	Drive Type	Slicing Volume per Day	Cheese Slicing	Blade Diameter	Max Slice	Produc D (Diameter)	t Cutting Ca W (Width)	pacity H (Height)
C9	Manua	I 1/4 HF	9 115-60-1	2	Belt	< 30 minutes	0 Not Recommended 100% Time	9'' (22.86 cm)	9/16" (1.43 cm)	6.25" (15.88 cm)	7.25" (18.42 cm)	6.5" (16.51 cm)

Cord & Plug: Attached 5.5 foot flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15

STANDARD FEATURES

Finish: Stain resistant, heavygauge, *anodized aluminum finish* is easy-to-clean.

Motor: 1/4 HP, Powerful fan cooled motor and permanently lubricated ball bearings ensure quiet operation. Thermal overload protection included.

Knife: 9" Hard chromed, special alloy hollow ground knife lasts longer and sharpens easily.

Manual Reset Button: Motor overload protection allows the operator to reset the slicer manually.

Top Mounted Sharpener: All metal construction and top mounted for easy access. Two stone, dual action design allows quick return to a razor sharp edge. Removable for cleaning.

On/Off Controls: Separate On/ Off push buttons are moisture protected and sanitation sealed.

Ball Bearing Chute Slide System: Ball bearing system ensures smooth and easy movement of the food chute assembly. **Knife Hub:** Knife hub bearings, belt and motor are fully enclosed, protecting them from moisture.

Knife Cover: Knife cover is designed to fit on the slicer only one way to ensure accurate placement every time.

Table Rod:Separate tablesupport rod is protected by thetable casting and cover.

Bottom Enclosure: Components are safeguarded by a cover, protecting them from food and other debris.

Slice Deflector: Deflector is securely fastened to the slicer; simple to remove without tools and easy to clean.

Rubber Feet: Supplied with nonslip rubber feet.

DIMENSIONS & SHIPPING INFORMATION

Carton reinforced for shipping. The weight and dimensions of reinforced carton are included below and may vary from shipment to shipment.

Model	Foot Print	Overall Dimensions	Net Weight	Shipping Dimensions	Shipping Weight
C9	14.5" D x 12.25" W	16.75" L x 19" W x 14.25" H	29.6 lbs.	19" L x 16" W x 15" H	33 lbs.
	(36.8 cm x 31.1 cm)	(42.5 cm x 48.3 cm x 36.2 cm)	(13.4 kg)	(48 cm x 41 cm x 38 cm)	(15 kg)



GLOBE FOOD EQUIPMENT COMPANY www.globeslicers.com

2153 Dryden Rd. Dayton, OH 45439 Phone: 937-299-5493 Phone: 800-347-5423 Fax: 937-299-4147

Freight Class 85

Printed in U.S.A. 1-2013

Specifications are subject to change without notice.