



Project _____

Item # _____

Quantity _____



GIR18

Induction Range 1800 Watts

Model

GIR18 - 1800W Countertop Induction Range



GLOBE FOOD EQUIPMENT COMPANY

Induction Range, 1800W

GIR18

Quality Construction

- Seamless stainless steel construction
- Durable ceramic cooktop
- Easy-to-clean controls and cooktop

Applications

- Omelets, eggs & bacon, seafood, poultry, burgers, delicate sauces, butter, chocolate, etc.

Standard Features

- 1800W, 120V
- 7 power levels
- Touch pad controls and 4 digit LED display
- Digital timer
- Proper pan detection and automatic empty pan safety shut-off
- Temperature settings from 140°F-460°F
- Error code alert display
- Adjustable foot for leveling unit
- Attached 5½-foot power cord and NEMA 5-15P plug, 5-20P plug (canada)

Warranty

- One-year parts and labor

Standard Equipment:

- Induction burner
- Adjustable digital timer, heat and temperature controls

- ✓ *Most energy efficient cooking in the world!*
- ✓ *No open flames*
- ✓ *Portable and light weight*
- ✓ *Stores away easily*

Approved By: _____

Date: _____



GLOBE FOOD EQUIPMENT COMPANY

www.globeslicers.com

2153 Dryden Rd.
Dayton, OH 45439
Phone: 937-299-5493
Phone: 800-347-5423
Fax: 937-299-4147



Induction Range, 1800W

GIR18



For Indoor Use Only

SPECIFICATIONS

- Seamless stainless steel construction
- Touch pad controls and 4 digit LED display
- Digital timer
- Proper pan detection and automatic empty pan safety shut-off
- Temperature settings from 140°F-460°F
- Error code alert display
- Adjustable foot for leveling unit
- Attached 5½-foot power cord and plug

| Model | Power Levels | Temp Settings | Cooking Surface | Electric | AMPs | Wattage | NEMA Plug Type |
|-------|--------------|---------------|-----------------|-----------|------|---------|--|
| GIR18 | 7 | 140°F-460°F | 4.75" to 10.25" | 120V/60Hz | 15 | 1800 W | 5-15P (U.S.) (Ⓢ) 5-20P (Canada) (Ⓢ) |

IMPORTANT: PERSONS WITH PACEMAKERS

Persons with pacemakers should stay at least 3 feet away from the induction range.

When using the induction range with the general public, a pacemaker notice should be posted near the equipment in use.

STANDARD EQUIPMENT:

Auto pan detection: Range detects if proper cookware/pan is placed on cooktop.

Automatic shut-off: Automatically shuts off when timer runs to "0".

Over-heat protection: Unit senses when the pan overheats and when the electrical components overheat; the unit then shuts off.

Digital timer: Set timer from 0-180 minutes.

Bright LED display: Bright 4 digit LED display for easy viewing.

Suitable Pans: Steel or cast iron, enameled cast iron, stainless steel and aluminum if marked "suitable for induction cooking", flat-bottom pans/pots with diameter of 12 to 26 cm or 4.75" to 10.25".

DIMENSIONS & SHIPPING INFORMATION

Cartons are reinforced for shipping. The weight and dimensions of reinforced cartons are listed below and may vary from shipment to shipment.

| Model | Foot Print | Overall Dimensions | Net Weight | Shipping Dimensions | Shipping Weight |
|-------|---------------------------------------|---|-----------------------|--|-----------------------|
| GIR18 | 12.87" W × 17.4" L (33 cm × 44 cm) | 17.4" L × 12.87" W × 4.33" H (44 cm × 33 cm × 11 cm) | 10.6 lbs. (4.8 kg) | 18.90" L × 15.16" W × 5.71" H (48 cm × 38.5 cm × 14.5 cm) | 14.4 lbs. (6.5 kg) |



GLOBE FOOD EQUIPMENT COMPANY

www.globeslicers.com

2153 Dryden Rd.
Dayton, OH 45439
Phone: 937-299-5493
Phone: 800-347-5423
Fax: 937-299-4147