Model B-6 Dual Decanter Brewer



Digitally controlled decanter brewer, holds brew temperature to <u>+</u> 1°F throughout brew cycle. Brew temperature, brew volume, operator defined pre-infusion/pulse brewing, energy savings, and low temp/no brew are programmable from the front of the machine.






Model B-6

Features

- Brewer has 6 decanter warmers 3 gallons of coffee holding capacity
- Brew Temperature Brewer will hold the brew temperature to +/-1°F during complete brew cycle
- Brew Volume Visual programming prevents multiple brew cycles to set volume
- Pre-Infusion/Pulse Brewing Allows brewer to extract up to 20% more coffee per batch of grounds
- Energy Savings/Coffee Old Warmers to be programmed to shut off and alert customer after a pre-determined hold time
- Low Temp/No Brew Allows the brew cycle to begin only when the water has reached optimum brewing temperature
- Cycle Counter stores number of brew cycles
- Settings Lock-out Prevents settings from being adjusted from the front of the machine



Front View

Side View

Specification	Model B-6
Electrical	120/240V, 4100W, 17.1A 120/208V, 3230W, 15.5A European voltages available
Brew Capacity	@ 240V: 16 @ 200V: 12
(decanters / hour) Water Line	@ 208V: 12 1/4" flare
Water Line Pressure	20 to 100 psi
Tank Drain	Yes
Tank Size	4.3 Gallons
Dimensions (H x W x D)	19" H x 16.2" W x 17.8" D (48 cm x 41 cm x 45 cm)
Ship Dimensions (H x W x D)	22" H x 24" W x 21" D (56 cm x 61 cm x 53 cm)
Weight	46 lbs. (21 kg)
Ship Weight	55 lbs. (25 kg)
Listings	UL, CUL, NSF, CE

Specifications are subject to improvement or change without notice.





Grindmaster® Coffee Grinders and Brewers • Espressimo® Espresso Machines • Crathco® Hot Beverage Dispensers Crathco® Cold and Frozen Beverage Dispensers • American Metal Ware® Coffee and Tea Systems Tel (502) 425-4776 • Fax (502) 425-4664 • 1-800-695-4500