## **Counter Top Gas Fryers**



#### Features

- Heavy duty 100% stainless steel construction for long life.
- √ 18 gauge Stainless Steel fry tank.
- ✓ Automatic temperature controls.
- ✓ Includes two fry baskets, crumb screen, and pressure regulator.
- ✓ Ball type slanted drain valve for fast draining.
- ✓ Basso Safety Pilot with high-limit control.
- ✓ GF-10 has a flat bottom, GF-16 and GF-28 are tube fired.
- ✓ 4" legs optional.

Model #	Fat Capacity	Depth	BTU/Hr Nat.; LP	Ship Weight	Use Fry Baskets
GF-10	13 lbs.	201/2"	26,000; 26,000	53 lbs.	V091A/V092A
GF-16	18 lbs.	21¾"	22,500; 18,000	60 lbs.	V091A/V092A
GF-28	28 lbs.	22"	45,000; 38,000	91 lbs.	V094A/V095A

Specify Natural or LP Gas Width: 121/4" GF28: 181/4" Height: 171/4" GF10: 141/2"

# **Counter Top Electric Fryers**

Removable Stainless Steel Tank

**Automatic Temperature Controls** 

### Features

- Heavy duty 100% stainless steel construction for long life.
- ✓ The EL120 can plug in anywhere.
- Heavy duty, high speed elements.
- ✓ Automatic temperature controls.
- Includes two fry baskets.



Model #	Fat Capacity	Width	Depth	Height	Electrical	Ship Weight	
EL-120	15 lbs.	12"	19½"	81/4"	120V, 18KW, 15A	29 lbs.	
EL-170 Same as EL-120 with 4" legs							
EL-250	15 lbs.	12"	19½"	81/4"	240V, 5.5KW, 22.9A 208V, 4.2KW, 20.2A	29 lbs.	
EL-270 Same as EL-250 with 4" legs							
EL-310*	45 lbs.	18"	21"	11½"	240V, 5.5KW, 22.9A 208V, 5.5KW, 26.4A	45 lbs.	
ELT-500	60 lbs.	25½"	201/2"	18½"	240V, 11KW, 46A 208V, 8.4KW, 40A	60 lbs.	

\* Specify voltage. 1 phase only. El-120/170 and EL-250/270 line cord included Use Fry Baskets: V091A and V092A except for EL310 use V077A and V078A

### **Counter Top Fry Baskets**







Part #	Fryer Type	Hook Placement	Depth	Width	Height
V006A	10 lb. gas	Front	83/4"	31/2"	41/2"
V091A	13, 18 lb. gas,	Right	10¾"	33/8"	33/4"
V092A	15 lb. electric	Left	1074	3.78	374
V077A	20 lb.	Right	107/8"	31/2"	49/16"
V078A	electric	Left	10 /8	3/2	4-/16
V094A	28 lb. gas	Right	103/16"	53/8"	43/4"
V095A	20 10. gas	Left	10-716	J /8	<b>+</b> 74