

• PRODUCT SPECIFICATIONS SHEETS



• Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

Self-Contained Remote	SC-CDS40E-8 R-CDS40E-8	SC-CDS40E-12 R-CDS40E-12
Length with (2) ends	100-1/2"	148-1/2"
Length without ends	96"	144"
Height with ends	53"	53"
Height without ends	52-1/2"	52-1/2"
Depth with ends	40"	40"
Depth without ends	39-1/2"	39-1/2"
Endless Design	YES	YES
(Dimensions are $\pm (-1/4)$ )		

• Specification subject to change without notice



# **Standard Specifications and Optional Features**

CONSTRUCTION  UL Classified to ANSI/NSF 7 Foamed in place CFC free foam Triple pane insulated front glass- 28"H Heavy gauge steel super structure Single duty display Endless design allows for continuous line up Drain is included for cleaning	FINISHES  Satin finish extrusion on doors and door tracks Designer white exterior front and ends Stainless steel mirror trim Stainless steel heavy gauge top- 20" W Rear of unit is stainless steel brush finish at top Bottom rear is designer white aluminum
INTERIOR Designer white interior ends Stainless steel heavy gauge mezzanine shelf (1row) Epoxy coated main deck shelves Air insulated baffle (prevents moisture from dripping into display area)	REFRIGERATION  Copevap system (eliminates need for condensate pan) R134a expansion valve system Gravity coil located at inside top of unit and Self contained system Automatic defrost controlled by time clock-(self contained units only) Pressure control maintains constant temperatures Remotes available
EXTERIOR  Double pane rear removable doors  Newly designed compression door jamb  Removable front grille allows for cleaning  Removable rear grille for easy servicing  2-1/4" removable end panels  Front bumper 1"- gray	LIGHTING 2 Rows of T12 lighting at top of unit
ELECTRICAL REQUIREMENTS  115V/60Hz/1Ph  Unit must be hard wired  UL/CUL listed  115V-12AMP general purpose receptacle (wired separately)	Important Note: All refrigerated cases are designed to operate in an environment of 75 degrees and 55% relative humidity.  Important Note: Product must be cooled before being displayed within the case.

#### **OPTIONAL FEATURES**

Scale stand	Drop work shelf
Paper cutter	Door locks
Stainless steel, laminate, or paint	Digital thermometer
Mirrored doors	Sandwich racks
Extra stainless steel mezzanine shelf	Salad pan settings
	Front bumpers 3"





## **Technical Data**

Model	Self contained	SC-CDS40E-8	SC-CDS40E-12
	Remote	R-CDS40E-8	R-CDS40E-12
Length with (2) ends Length without ends Height with ends Height without ends Depth with ends Depth without ends Endless design (Dimensions are +/- 1/4")		100-1/2" 96" 53" 52-1/2" 40" 39-1/2" YES	148-1/2" 144" 53" 52-1/2" 40" 39-1/2" YES
Operating temperature Refrigerant (expansion valve) Compressor size- HP Pressure control settings @ 75°F, 55%RH	Self contained Self contained CUT IN CUT OUT	36°F to 40°F R134a 1/2 30 12	36°F to 40°F R134a 3/4 30 12
Defrost per day (24 hours) BTU's at +20°F Evap. Temp. Voltage Amperage Amperage- lights only Cord and plug	Air Defrost Remote  Self Contained Remote	1 per day 2800 115V 11.2A 1.6A No	1 per day 4200 115V 17.4A 2.4A No
Exterior color Interior color Inside end panels Floors # of top doors Door size # of coils Bottom storage Front glass # of main deck shelves Shelf size Cubic capacity (ft³) Mezzanine- shelf		White Stainless White White 4 20-1/2"X23-1/2" 1 No 28"X94-11/16" 4 23-1/2"X32-5/8" 49 Standard	White Stainless White White 4 31"X23-1/2" 1 No 28"X142-11/16" 6 23-1/2"X32-5/8" 74 Standard

### SHIPPING INFORMATION

Height Depth Length Gross weight	Self contained Remote	58" 47" 109" 983# 890#	58" 47" 157" 1396# 1325#
Cubic feet	Remote	170ft <sup>3</sup>	245ft <sup>3</sup>

- · Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- · Cases are equipped with washout drains; check your local building codes for connection requirements.
- · Specification subject to change without notice

## Technical Data • Side View • Plan View





