

• PRODUCT SPECIFICATIONS SHEETS



• Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

Self-Contained Remote	SC-CFS40E-8 R-CFS40E-8	SC-CFS40E-12 R-CFS40E-12
Length with (2) ends	100-1/2"	148-1/2"
Length without ends	96"	144"
Height with ends	53"	53"
Height without ends	52-1/2"	52-1/2"
Depth with ends	40"	40"
Depth without ends	39-1/2"	39-1/2"
Endless Design	YES	YES
(Dimensions are $\pm /-1/4$ ")		

• Specification subject to change without notice



Standard Specifications and Optional Features

CONSTRUCTION UL Classified to ANSI/NSF 7 Foamed in place CFC free foam Triple pane insulated front glass- 28"H Heavy gauge steel super structure Single duty display Endless design allows for continuous line up Drain is included for cleaning	FINISHES Satin finish extrusion on doors and door tracks Designer white exterior front and ends Stainless steel mirror trim Stainless steel heavy gauge top- 20" W Rear of unit is stainless steel brush finish at top Bottom rear is designer white aluminum
INTERIOR Designer white interior ends Air insulated baffle (prevents moisture from dripping into display area) Stainless steel individual ice pans	REFRIGERATION Copevap system (eliminates need for condensate pan) R134a expansion valve system Gravity coil located at inside top of unit and Self contained system Automatic defrost controlled by time clock-(self contained units only) Pressure control maintains constant temperatures Remotes available
EXTERIOR Double pane rear removable doors Newly designed compression door jamb Removable front grille allows for cleaning Removable rear grille for easy servicing 2-1/4" removable end panels Front bumper 1"- gray	LIGHTING 2 Rows of T12 lighting at top of unit
ELECTRICAL REQUIREMENTS 115V/60Hz/1Ph Unit must be hard wired UL/CUL listed 115V-12AMP general purpose receptacle (wired separately)	Important Note: All refrigerated cases are designed to operate in an environment of 75 degrees and 55% relative humidity. Important Note: Product must be cooled before being displayed within the case. ICE REQUIRED (32 lbs per foot)

OPTIONAL FEATURES

Paper cutter Do Stainless steel, laminate, or paint Dig	rop work shelf oor locks rigital thermometer ront bumpers 3"
--	---





Technical Data

Model	Self contained	SC-CFS40E-8	SC-CFS40E-12
	Remote	R-CFS40E-8	R-CFS40E-12
Length with (2) ends Length without ends Height with ends Height without ends Depth with ends Depth without ends Endless design (Dimensions are +/- 1/4")		100-1/2" 96" 53" 52-1/2" 40" 39-1/2" YES	148-1/2" 144" 53" 52-1/2" 40" 39-1/2" YES
Operating temperature Refrigerant (expansion valve) Compressor size- HP Pressure control settings @ 75°F, 55%RH	Self contained Self contained	38°F to 40°F R134a 1/3 30	38°F to 40°F R134a 1/2 30 15
Defrost per day (24 hours) BTU's at +20°F Evap. Temp. Voltage Amperage Amperage- lights only Cord and plug	CUT OUT Air Defrost Remote Self Contained Remote	15 1 per day 1640 115V 9.1A 1.6A No	15 1 per day 2460 115V 13.8A 2.4A No
Exterior color Interior color Inside end panels Floors # of top doors Door size # of coils Bottom storage Front glass # of ice pans Cubic capacity (ft³) Mezzanine- shelf		White Stainless White White 4 20-1/2"X23-1/2" 1 No 28"X94-11/16" 4 49 Optional	White Stainless White White 4 31"X23-1/2" 1 No 28"X142-11/16" 5 74 Optional

SHIPPING INFORMATION

Height Depth Length Gross weight	Self contained Remote	58" 47" 109" 983# 890#	58" 47" 157" 1396# 1325#	
Cubic feet		170ft ³	245ft ³	

- · Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- · Cases are equipped with washout drains; check your local building codes for connection requirements.
- · Specification subject to change without notice



Technical Data • Side View • Plan View

