

Open Merchandisers - Ovation Series Endless Design 72"H - Meat

• PRODUCT SPECIFICATIONS SHEETS



• Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

Self-Contained Remote	SC-OM30E-3-LS R-OM30E-3-LS	SC-OM30E-4-LS R-OM30E-4-LS	SC-OM30E-6-LS R-OM30E-6-LS
Length with ends	39"	51"	75"
Length without ends	36"	48"	72"
Height with ends	72"	72"	72"
Depth with ends	30"	30"	30"
(Dimensions are +/-1/4")			

• Specification subject to change without notice



Open Merchandisers - Ovation Series Endless Design 72"H - Meat

Standard Specifications and Optional Features

CONSTRUCTION Foamed in place CFC free foam Heavy gauge steel super structure Multi deck Endless design allows for continuous line up	FINISHES Designer white or black end panels Designer white or black front bumper Designer white or black end trim Designer white or black rear
INTERIOR Designer white or black end panels Removable designer white or black floor pans Designer white or black perforated rear wall (for even air distribution) Full length lighting at top of unit 1 level of 12" lighted shelving 2 levels of 14" lighted shelving 3 levels of product display Stylish tag molding on each shelf	REFRIGERATION R404A expansion valve system Low velocity fans located below deck area (to insure even flow of air) Pressure control maintains constant temperatures Automatic defrost controlled by time clock (self contained units only) Air screen technology Self contained system Copeland hermetic unit Remotes available
EXTERIOR Designer white or black ends and front Designer white or black bumper Designer white or black end trim Removable front grille for cleaning and servicing Plexiglas on end panel	LIGHTING 1 row at inside top of unit 3 rows of lighted shelves
ELECTRICAL REQUIREMENTS Unit must be hard wired UL/CUL listed See Tech page for details on voltage	Important Note: All refrigerated cases are designed to operate in an environment of 75 degrees and 55% relative humidity. Important Note: Product must be cooled before being displayed within the case. Important Note: DRAIN IS REQUIRED

OPTIONAL FEATURES

Night covers	Stainless steel, laminate or paint
Peg bars	Security cover
Condensate pan (4' case only)	Plexiglas divider for line ups
Insulated divider for line ups	Digital thermometer
Electronic control system	

(ALL WHITE OR ALL BLACK, NO EXTRA CHARGE—IF COLORS ARE MIXED AN ADDITIONAL CHARGE WILL APPLY)





Open Merchandisers - Ovation Series Endless Design 72"H - Meat

Technical Data

Model	Self contained	SC-OM30E-3-LS	SC-OM30E-4-LS	SC-OM30E-6-LS
	Remote	R-OM30E-3-LS	R-OM30E-4-LS	R-OM30E-6-LS
Length with ends Length without ends Height with ends Depth with ends (Dimensions are +/- 1/4")		39" 36" 72" 30"	51" 48" 72" 30"	75" 72" 72" 30"
Operating temperature Refrigerant (expansion valve) Compressor size- HP Pressure control settings @ 75°F, 55%RH Defrost per day (24 hours) BTU's at +20°F Evap. Temp. Voltage Amperage Amperage, lights & fans Cord and plug	Self contained Self contained CUT IN CUT OUT Air Defrost Remote Self contained Remote		34°F to 38°F R404A 3/4 87 43 3 @ 30 min. 5600 115/208-230V 11.3A 2.2A No	34°F to 38°F R404A 1 87 43 3 @ 30 min. 8400 115/208-230V 13.7A 2.8A No
Exterior color Interior color Inside end panels Floors Cubic capacity		White or Black White or Black White or Black White or Black	White or Black White or Black White or Black White or Black	White or Black White or Black White or Black White or Black

(ALL WHITE OR ALL BLACK, NO EXTRA CHARGE—IF COLORS ARE MIXED AN ADDITIONAL CHARGE WILL APPLY)

SHIPPING INFORMATION

Height		76"	76 "	76 "
Depth		44"	44"	44"
Length		61"	61"	87"
Gross weight	Self contained	535#	615#	860#
	Remote	505#	570#	735#
Cubic feet	Kemote	115ft ³	115ft ³	166ft ³

- · Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- · Cases are equipped with drains; check your local building codes for connection requirements.
- · Specification subject to change without notice



Open Merchandisers - Ovation Series Endless Design 72"H - Meat

Technical Data • Side View • Plan View

