

## RIF Endless Design - Glass Door Reach In Freezers with 24" Wide Doors

• PRODUCT SPECIFICATIONS SHEETS



- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

Remote	RIF2-24	RIF3-24	RIF4-24	RIF5-24
Length with ends	54-7/8"	78-7/8"	102-3/8"	126-1/8"
Height	78-1/2"	78-1/2"	78-1/2"	78-1/2"
Depth with ends	35-1/2"	35-1/2"	35-1/2"	35-1/2"
(Dimensions are +/-1/4")				

- Specification subject to change without notice

## RIF Endless Design - Glass Door Reach In Freezers with 24" Wide Doors

### Standard Specifications and Optional Features

<p><b>CONSTRUCTION</b>          UL Classified to ANSI/NSF 7          Heavy duty construction          CFC free foamed in place insulation          2, 3, 4, or 5 door models available          Inset door assembly          Endless for continuous line ups</p>	<p><b>FINISHES</b>          Frame assembly and door - Anthony style 101          Exterior-designer white          Interior-designer white</p>
<p><b>INTERIOR</b>          White ends          Back is a combination of <i>white and perforated aluminum</i>          Removable floor racks          5 heavy duty white epoxy shelves per door</p>	<p><b>REFRIGERATION</b>          Remote with R404A expansion valve          Coil and fans located below floor pans</p>
<p><b>EXTERIOR</b>          White aluminum ends and fronts          Triple pane glass doors 24"X63"          Black kick plate</p>	<p><b>LIGHTING</b>          60" fluorescent lamps          2 Dr = 3 lights          3 Dr = 4 lights          4 Dr = 5 lights          5 Dr = 6 lights</p>
<p><b>ELECTRICAL REQUIREMENTS</b>          Electric defrost and defrost termination              Standard 230V/60Hz/3Ph          Fans and lighting              115V/60Hz/1ph          Unit must be hard wired          UL/CUL listed</p>	<p><b><i>Important Note: All refrigerated cases are designed to operate in an environment of 75 degrees and 55% relative humidity.</i></b></p> <p><b><i>Important Note: Product must be cooled before being displayed within the case.</i></b></p>

### OPTIONAL FEATURES

<p>Stainless steel, laminate or paint          Digital thermometer          Door swing change          Insulated divider          Plexiglas divider</p>	<p>Door locks          Special door frames          Hot gas defrost          Temperature control thermostat          Joint kit</p>
---	--



## RIF Endless Design - Glass Door Reach In Freezers with 24" Wide Doors

### Technical Data

Model	Remote	RIF2-24	RIF3-24	RIF4-24	RIF5-24
Length Height Depth (Dimensions are +/- 1/4")		54-7/8" 78-1/2" 35-1/2"	78-7/8" 78-1/2" 35-1/2"	102-3/8" 78-1/2" 35-1/2"	126-1/8" 78-1/2" 35-1/2"
Operating temperature Refrigerant (expansion valve) Defrost per day (24 hours) BTU's at -25°F Evap. Temp. BTU's at -35°F Evap. Temp. Voltage Amperage Cord and plug	1 Defrost	0°F to -10°F R404A 1 3840 3980 115/230V 9.1/5.4A No	0°F to -10°F R404A 1 5577 5829 115/230V 10.8/8.2A No	0°F to -10°F R404A 1 7173 7500 115/230V 15.6/11.1A No	0°F to -10°F R404A 1 8829 9231 115/230V 18.0/13.9A No
Exterior color Interior color Inside end panels Floor-removable deck pans Drain required Total shelves Door size		White White White White Yes 10 24"X63"	White White White White Yes 15 24"X63"	White White White White Yes 20 24"X63"	White White White White Yes 25 24"X63"

### SHIPPING INFORMATION

Height		83"	83"	83"	83"
Length		61"	86"	107"	134"
Depth		43"	43"	43"	43"
Gross weight		729#	1031#	1333#	1635#
Cubic feet		125ft <sup>3</sup>	177ft <sup>3</sup>	221ft <sup>3</sup>	276ft <sup>3</sup>

- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- Specification subject to change without notice

## RIF Endless Design - Glass Door Reach In Freezers with 24" Wide Doors

### Technical Data • Side View • Plan View

