

• PRODUCT SPECIFICATIONS SHEETS



• Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

Self-Contained Remote		SC-OP30E-4L-LS R-OP30E-4L-LS		
Length with ends	39"	51"	75"	99"
Length without end	l <b>s</b> 36"	48"	72"	96"
Height with ends	60"	60"	60"	60"
Depth with ends	30"	30"	30"	30"
(Dimensions are +/-1,	(4")			

• Specification subject to change without notice



# **Standard Specifications and Optional Features**

CONSTRUCTION  UL Classified to ANSI/NSF 7 Foamed in place CFC free foam Heavy gauge steel super structure Multi deck Endless design allows for continuous line up	FINISHES  Designer white or black end panels Designer white or black front bumper Designer white or black end trim Designer white or black rear
INTERIOR  Designer white or black end panels Removable designer white or black floor racks Designer white or black perforated rear wall (for even air distribution) Full length lighting at top of unit 1 level of 14" shelving with product stops Full length mirror to enhance product display Stylish tag molding on shelf	REFRIGERATION  R404A expansion valve system  Low velocity fans located below deck area (to insure even flow of air)  Pressure control maintains constant temperatures  Automatic defrost controlled by time clock (self contained units only)  Air screen technology  Self contained system  Copeland hermetic unit  Remotes available
EXTERIOR  Designer white or black ends and front Designer white or black bumper Designer white or black end trim Removable front grille for cleaning and servicing Plexiglas on end panel	LIGHTING  1 row at inside top of unit 1 lighted shelf with product stop
ELECTRICAL REQUIREMENTS Unit must be hard wired UL/CUL Listed See technical page for voltage	Important Note: All refrigerated cases are designed to operate in an environment of 75 degrees and 55% relative humidity.  Important Note: DRAIN IS REQUIRED

(ALL WHITE OR ALL BLACK, NO EXTRA CHARGE-IF COLORS ARE MIXED AN ADDITIONAL CHARGE WILL APPLY)

#### **OPTIONAL FEATURES**

Night cover	Stainless steel, laminate or colors
Peg bars	Security cover
Condensate pan (4' case only)	Plexiglas divider for line ups
Insulated divider for line ups	Digital thermometer
Electronic control system	





#### **Technical Data**

Model	Self contained	SC-OP30E-3L-LS	SC-OP30E-4L-LS	SC-OP30E-6L-LS	SC-OP30E-8L-LS
	Remote	R-OP30E-3L-LS	R-OP30E-4L-LS	R-OP30E-6L-LS	R-OP30E-8L-LS
Length with ends Length without ends Height with ends Depth with ends (Dimensions are +/- 1/4")		39" 36" 60" 30"	51" 48" 60" 30"	75" 72" 60" 30"	99" 96" 60" 30""
Operating temperature Refrigerant (expansion valve) Compressor size- HP Pressure control settings @ 75°F, 55%RH  Defrost per day (24 hours) BTU's at +20°F Evap. Temp. Voltage Amperage Amperage, lights & fans Cord and plug	Self contained Self contained CUT IN CUT OUT Air Defrost Remote Self contained Remote		38°F to 41°F R404A 1/2 88 54 3 @ 30 min. 3200 115V 12.4A 1.7A No	38°F to 41°F R404A 1/2 88 54 3 @ 30 min. 4800 115V 13.5A 2.0A No	38°F to 41°F R404A 3/4 88 54 3 @ 30 min. 6400 115/208-230V 12.5A 3.4A No
Exterior color Interior color Inside end panels Floors		White or Black White or Black White or Black White or Black	White or Black White or Black White or Black White or Black	White or Black White or Black White or Black White or Black	White or Black White or Black White or Black White or Black

(ALL WHITE OR ALL BLACK, NO EXTRA CHARGE—IF COLORS ARE MIXED AN ADDITIONAL CHARGE WILL APPLY)

#### SHIPPING INFORMATION

Height Depth		65" 44"	65" 44"	65" 44"	65" 44"
Length Gross weight	Self contained Remote	61" 495# 370#	61" 575# 450#	87" 800# 675#	109" 1025# 875#
Cubic feet		99ft³	99ft <sup>3</sup>	142ft <sup>3</sup>	177ft <sup>3</sup>

- · Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- · Cases are equipped with drains; check your local building codes for connection requirements.
- Specification subject to change without notice



#### Technical Data • Side View • Plan View

