

• PRODUCT SPECIFICATIONS SHEETS



• Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

Self-Contained	SC-OS30E-3	SC-OS30E-4	SC-OS30E-6
Remote	R-OS30E-3	R-OS30E-4	R-OS30E-6
Length with ends	39"	51"	75"
Length without ends	36"	48"	72"
Height with ends	44"	44"	44"
Height without ends	43-7/8"	43-7/8"	43-7/8"
Depth with ends	30"	30"	30"
Depth without ends	29-1/2"	29-1/2"	29-1/2"
Endless Design	Yes	Yes	Yes
(Dimensions are $+/-1/4$ ")			

• Specification subject to change without notice



### **Standard Specifications and Optional Features**

CONSTRUCTION  UL Classified to ANSI/NSF 7 Foamed in place CFC free foam Heavy gauge steel super structure Endless design allows for continuous line up Wide view Plexiglas on front and ends	FINISHES  Designer white or black end panels Designer white or black front bumper Designer white or black rear Designer white or black end trim
INTERIOR  Designer white or black end panels Removable designer white or black floor racks Designer white or black perforated rear wall (for even air distribution) 3 tier step rack	REFRIGERATION R134a expansion valve system Automatic condensate Low velocity fans located below deck area (to insure even flow of air) Pressure control maintains constant temperatures Auto defrost controlled by time clock (self contained units only) Air screen technology Self contained system Copeland hermetic unit Remotes available
EXTERIOR  Designer white or black ends and front Designer white or black bumper Designer white or black end trim Removable front grille for cleaning and servicing 7" of Plexiglass on end panel	LIGHTING
ELECTRICAL REQUIREMENTS 115V/60Hz/1Ph Cord and plug provided UL/CUL listed	Important Note: All refrigerated cases are designed to operate in an environment of 75 degrees and 55% relative humidity.  Important Note: Product must be cooled before being displayed within the case.

(ALL WHITE OR ALL BLACK, NO EXTRA CHARGE—IF COLORS ARE MIXED AN ADDITIONAL CHARGE WILL APPLY)

#### **OPTIONAL FEATURES**

Remote available	Stainless steel, laminate or paint
Rear grille	Night cover
Digital thermometer	Peg bars
Sandwich/ fruit racks	Casters





### **Technical Data**

Model #	Self contained	SC-OS30E-3	SC-OS30E-4	SC-OS30E-6
	Remote	R-OS30E-3	R-OS30E-4	R-OS30E-6
Length with ends Length without ends Height with ends Height without ends Depth with ends Depth without ends (Dimensions are +/- 1/4")		39" 36" 44" 43-7/8" 30" 29-1/2"	51" 48" 44" 43-7/8" 30" 29-1/2"	75" 72" 44" 43-7/8" 30" 29-1/2"
Operating temperature Refrigerant-(expansion valve) Compressor size- HP Pressure control settings at 75°F, 55% RH	Self contained Self contained CUT IN CUT OUT		36°F to 40°F R134a 1/2 29 12	36°F to 40°F R134a 3/4 29 12
Defrost per day (24 hours) BTU's at +20°F Evap. Temp. Voltage Amperage Amperage Cord and plug	Air Defrost Remote Self contained Remote	6 @ 20 minutes 3100 115V 12.0A 0.7A Yes(15A)	6 @ 20 minutes 4130 115V 13.1A 1.4A Yes(20A)	6 @ 20 minutes 6200 115V 16.0A 1.4A Yes(20A)
Exterior color Interior color Inside end panels Floors		White or Black White or Black White or Black White or Black	White or Black White or Black White or Black White or Black	White or Black White or Black White or Black White or Black

(ALL WHITE OR ALL BLACK, NO EXTRA CHARGE—IF COLORS ARE MIXED AN ADDITIONAL CHARGE WILL APPLY)

#### SHIPPING INFORMATION

Height		49"	49"	49"
Depth		44"	44"	44"
Length		61"	61"	87"
Gross weight	Self contained	330#	360#	495#
	Remote	205#	235#	345#
Cubic feet	Remote	76ft <sup>3</sup>	76ft <sup>3</sup>	109ft <sup>3</sup>

- · Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- · Cases are equipped with drains; check your local building codes for connection requirements.
- · Specification subject to change without notice



#### Technical Data • Side View • Plan View

