

Job

Item #

Metro C5 Pizza Series Heated Holding Cabinet

- Control: The C5 Pizza Series controls temperature for safe and hot holding of pizza and other foods. Temperature is displayed on an "always-on" analog thermometer for continuous monitoring of the cabinet temperature, even when turned off or unplugged.
- Performance: Rapid heat-up and recovery times are achieved with a thermostatically controlled ducted heating system. All models are Energy Star.
- Sizes: C5 Pizza Series cabinets are available in Full Height (74.75") and 1/2 Height (44.75") sizes.
- Doors: C5 Pizza Series cabinets are all available with a choice of insulated solid or clear double pane, insulated Low-E, tempered glass doors. Clear doors provide visibility of the contents of the cabinet without the heat loss associated with opening the door. Full Height cabinets are configured with Dutch style doors. All doors lift off and are field reversible.
- Pass-Thru: Pass-thru models are available for applications that require access from both the front and the back of the cabinet.
- Capacity: C5 Pizza Series cabinets are available configured with Universal Wire Slides or with Wire Shelves. Universal slides hold (2) 16" Pizza boxes front-to-back, 18" x 26" sheet pans, or (2) 12" x 20" steam table pans front-to-back on adjustable 11/2" increments. Wire shelves accommodate just about anything including small boxes and odd-sized pans or containers. Wire shelves and universal slides work together and can be intermixed when ordered as accessories.
- Reliability: Reliability and durability are designed into all C5 cabinets from the ground up. High-quality components and robust construction provide a long life of service and worry-free use.
- Top-Mounted Controls: Ergonomic user-friendly controls are mounted at the top of the cabinet for easier access, better readability, to prevent damage, and to simplify cleaning.
- Passive Humidity: An integral water pan system can be used to add humidity to the cabinet environment, improving the quality of food products that require a moist holding environment.
- Construction: Available in both stainless steel and aluminum.

Options/Accessories:

- Pizza Wire Shelf (C5-ZSHELF)
- Stainless Steel Legs (C5-SSLEGS)
- Universal Slide Pair (C5-ZUSLIDECPR)
- Right Angle Plug (C5-RTANGPLG)
- Twist Lock Plug (C5-RTWSTPLG)
- Flush Door Latch (C5-LATCHFLUSH)
- Twist Lock Flush Door Latch (C5-LATCHTWST)
- Key Lock Flush Door Latch (C5-LATCHLOCK)
- 6" Casters (C5-6CASTER)
- Rear Rigid Casters (C5-5RDGCSTR)
- Corner Bumpers/Drip Trough (C5-BUMPDRIP)
- Left Hand Hinging (DD3768)
- Control Panel Cover (C5-COVER)

Note: Add an "A" to the end of the cabinet part number when ordering accessories.



Clear Doors







Full Height Dutch

Solid Doors



1/2 Height

Clear Doors



Metro

റ5

NZ2

Series

Heated Holding Cabine

1/2 Height Solid Doors





InterMetro Industries Corporation

North Washington Street Wilkes-Barre, PA 18705 www.metro.com



Metro C5 Pizza Series Heated Holding Cabinet

Specifications

- **Cabinet Material:** Type 304 stainless steel; 20-gauge polished exterior; 22-gauge interior, or .063" aluminum, brushed exterior, natural interior.
- Insulation: Full perimeter, 1" thick, high-density fiberglass. R Value = 4.2
- **Casters:** Four casters with 5" donut neoprene wheel, double ball bearing swivel, ball bearing axle, nickel plated, two with brake.
- **Solid Doors:** Fully insulated, double-panel, Type 304, 20-gauge polished exterior, 22-gauge interior stainless steel or .063" aluminum, brushed exterior, natural interior.
- **Hinges:** Self-closing, lift-off, double hinged, with long-life nylon bearings.
- **Gaskets:** High temperature, cabinet mounted, Santoprene gaskets.
- Latches: Chrome plated, high-strength magnetic pull latch with lever-action release.
- Handles: Four built-in polymer handles.
- **Universal Slides:** Universal wire slides; ¹/₄" diameter nickel-chrome wire adjustable on 1¹/₂" increments. 16-gauge, Type 304, stainless steel vertical standards.
- Wire Shelves: Stainless steel wire shelves adjustable on 11/2" increments.

Cabinet Capacities:

	Slide	16" Pizza	18" x 26"	12" x 20" x 2 ¹ /2"	Wire
Cabinet Size	Levels	Box	Sheet Pan	Steam Table Pan	Shelves
Full Height/Dutch	17	34	17	34	4
¹ / ₂ Height	8	16	8	16	2

Capacity based on 3 slide spacing, (1) sheet pan per level, (2) 16* pizza boxes per level, or (2) steam table pans per level.

Display and Controls: Analog cabinet thermometer with independent thermostat control knob.


- Heat Generation System: Thermostatically controlled 1950 Watt heating element, ball bearing blower motor, and ducted air system.
- **Cord:** 7¹/₂' cord with NEMA 5-20P plug. Cord mounted on top (Full Height & Pass Thru) or back (¹/₂ Height) can be field reversed.
- Thermal Performance: 70° F to 200° F operating temperature range.
- Power Requirements: 2000 Watts, 120 Volts, 60 Hz., single phase, 20 Amp. Service (16 Amps Draw).

Part Numbers

FULL HEIGHT CA		_				
Part Number	Material	Doors	Holding Style			
C5Z69-SDS-U	Stainless	Dutch Solid	Universal Slides			
C5Z69-SDS-S	Stainless	Dutch Solid	(4) Shelves			
C5Z69-SDC-U	Stainless	Dutch Clear	Universal Slides			
C5Z69-SDC-S	Stainless	Dutch Clear	(4) Shelves			
C5Z69-NDS-U	Aluminum	Dutch Solid	Universal Slides			
C5Z69-NDS-S	Aluminum	Dutch Solid	(4) Shelves			
C5Z69-NDC-U	Aluminum	Dutch Clear	Universal Slides			
C5Z69-NDC-S	Aluminum	Dutch Clear	(4) Shelves			
FULL HEIGHT, PASS THRU CABINETS						
Part Number	Material	Doors	Holding Style			
C5Z69-SDC-UPDC	Stainless	Dutch Clear/Dutch Clear	Universal Slides			
C5Z69-SDC-SPDC	Stainless	Dutch Clear/Dutch Clear	(4) Shelves			
C5Z69-NDC-UPDC	Aluminum	Dutch Clear/Dutch Clear	Universal Slides			
C5Z69-NDC-SPDC	Aluminum	Dutch Clear/Dutch Clear	(4) Shelves			
1/2 HEIGHT CABIN						
Part Number	Material	Doors	Holding Style			
C5Z65-SFS-U	Stainless	Full Solid	Universal Slides			
C5Z65-SFS-U C5Z65-SFS-S	Stainless Stainless	Full Solid Full Solid	(2) Shelves			
C5Z65-SFS-S	Stainless	Full Solid	(2) Shelves			
C5Z65-SFS-S C5Z65-SFC-U	Stainless Stainless	Full Solid Full Clear	(2) Shelves Universal Slides			
C5Z65-SFS-S C5Z65-SFC-U C5Z65-SFC-S	Stainless Stainless Stainless	Full Solid Full Clear Full Clear	(2) Shelves Universal Slides (2) Shelves			
C5Z65-SFS-S C5Z65-SFC-U C5Z65-SFC-S C5Z65-NFS-U	Stainless Stainless Stainless Aluminum	Full Solid Full Clear Full Clear Full Solid	(2) Shelves Universal Slides (2) Shelves Universal Slides			
C5265-SFS-S C5265-SFC-U C5265-SFC-S C5265-SFC-S C5265-NFS-U C5265-NFS-S	Stainless Stainless Stainless Aluminum Aluminum	Full Solid Full Clear Full Clear Full Solid Full Solid	(2) Shelves Universal Slides (2) Shelves Universal Slides (2) Shelves			
C5265-SFS-S C5265-SFC-U C5265-SFC-S C5265-NFS-U C5265-NFS-S C5265-NFC-U C5265-NFC-U C5265-NFC-S Y ₂ HEIGHT, PASS-	Stainless Stainless Stainless Aluminum Aluminum Aluminum THRU CABIN	Full Solid Full Clear Full Clear Full Solid Full Solid Full Clear Full Clear Full Clear ETS	 (2) Shelves Universal Slides (2) Shelves Universal Slides (2) Shelves Universal Slides (2) Shelves (2) Shelves 			
C5265-SFS-S C5265-SFC-U C5265-SFC-S C5265-NFS-U C5265-NFS-S C5265-NFC-U C5265-NFC-U C5265-NFC-S	Stainless Stainless Stainless Aluminum Aluminum Aluminum	Full Solid Full Clear Full Clear Full Solid Full Solid Full Clear Full Clear	(2) Shelves Universal Slides (2) Shelves Universal Slides (2) Shelves Universal Slides			
C5265-SFS-S C5265-SFC-U C5265-SFC-S C5265-NFS-U C5265-NFS-S C5265-NFC-U C5265-NFC-U C5265-NFC-S Y ₂ HEIGHT, PASS-	Stainless Stainless Stainless Aluminum Aluminum Aluminum THRU CABIN	Full Solid Full Clear Full Clear Full Solid Full Solid Full Clear Full Clear Full Clear ETS	 (2) Shelves Universal Slides (2) Shelves Universal Slides (2) Shelves Universal Slides (2) Shelves (2) Shelves 			
C5265-SFS-S C5265-SFC-U C5265-SFC-S C5265-NFS-U C5265-NFS-S C5265-NFC-U C5265-NFC-U C5265-NFC-S Y ₂ HEIGHT, PASS- Part Number	Stainless Stainless Stainless Aluminum Aluminum Aluminum THRU CABIN Material	Full Solid Full Clear Full Clear Full Solid Full Solid Full Clear Full Clear ETS Doors	(2) Shelves Universal Slides (2) Shelves Universal Slides (2) Shelves Universal Slides (2) Shelves Holding Style			
C5265-SFS-S C5265-SFC-U C5265-SFC-S C5265-NFS-U C5265-NFS-S C5265-NFC-U C5265-NFC-U C5265-NFC-S Y ₂ HEIGHT, PASS- Part Number C5265-SFC-UPFC	Stainless Stainless Stainless Aluminum Aluminum Aluminum HIRU CABIN Material Stainless	Full Solid Full Solid Full Clear Full Solid Full Solid Full Clear Full Clear ETS Doors Full Clear/Full Clear	(2) Shelves Universal Slides (2) Shelves Universal Slides (2) Shelves Universal Slides (2) Shelves Holding Style Universal Slides			

Note: Add an "A" to the end of the cabinet part number when ordering accessories.

Dimensions



Metro Heated cabinets are for hot food holding applications only.

All Metro Catalog Sheets are available on our Web Site: www.metro.com



InterMetro Industries Corporation

North Washington Street, Wilkes-Barre, PA 18705 Phone: 570-825-2741 Fax: 570-825-2852

For Product Information: U.S. and Canada: 1.800.992.1776 Outside U.S. and Canada: www.metro.com/contactus L03-266 Printed in U.S.A. Rev. 10/11 Information and specifications are subject to change without notice. Please confirm at time of order.

Copyright © 2011 InterMetro Industries Corp