

# FRYERS AND DUMP STATIONS



JTFF-40-18 with stainless steel riser

MODEL NO.	DESCRIPTION
JTFF-25-12	ONE 25 LB. TANK, 12" WIDE
🖵 JTFF-225-24	TWO 25 LB. TANKS, 24 <sup>"</sup> WIDE
🖵 JTFF-40-18	ONE 40 LB. TANK, 18" WIDE
🖵 JTFF-240-36	TWO 40 LB. TANKS, 36" WIDE
JTDS-18	DUMP STATION, 18" WIDE

# STANDARD FEATURES

### FRYERS

- Variable size multi-point gas connection-see utility information for details
- Stainless steel tank
- Stainless steel front, sides and top
- 1-1/4" quick drain port
- "ACCU-SENSE" thermostat for precise heat control
- Heavy gauge stainless steel fryer baskets
- Stainless steel adjustable 6" legs
- Stainless steel 6" plate shelf
- Stainless steel door
- "ASTRO-THERM" heating tubes allow fast recovery time, and lower frying temperatures

### DUMP STATIONS

• Stainless steel door

### AVAILABLE OPTIONS

- □ When stainless steel is specified, Jade Range, LLC. uses heavy gauge stainless steel
- □ Stainless steel high riser
- □ Stainless steel double high riser
- □ Cap and cover manifold. Left □ Right □

### ACCESSORIES


- $\Box$  6" casters, front two locking (5" diameter wheel)
- $\Box$  36" flex hose with quick disconnect (3/4" connection)
- □ 48" flex hose with quick disconnect (3/4" connection)
- □ 1" gas pressure regulator (specify gas type)
- □ 1-1/4" gas pressure regulator (specify gas type)



JADE RANGE, LLC., A MIDDLEBY COMPANY • 2650 Orbiter Street • Brea, CA 92821 • PHONE: 800-884-5233 FAX: 714-961-2550 Note: In line with their policy to continually improve products, Jade reserves the right to change materials and specifications without notice. PRINTED IN USA JADE



# FRYERS AND DUMP STATIONS



MODEL	BTUS	WIDTH	DEPTH	HEIGHT	APPX. SHP. WT.
JTFF-25-12	60,000	12"	38"	36.5"	240 LBS
JTFF-225-24	120,000	24"	38"	36.5"	300 LBS
JTFF-40-18	110,000	18"	38"	36.5"	280 LBS
JTFF-240-36	220,000	36"	38"	36.5"	490 LBS
JTDS-18	N/A	18"	38"	36.5"	100 LBS

### **DESCRIPTION:**

Fryers and Dump Stations. To be Model #\_\_\_\_\_, manufactured by Jade Range, LLC. Standard features include variable size multipoint gas connection—see utility information for details, stainless steel tank, stainless steel front, sides and top, 1-1/4" quick drain port, "ACCU-SENSE" thermostat for precise heat control, heavy gauge stainless steel fryer baskets, stainless steel adjustable 6" legs, stainless steel 6" plate shelf, stainless steel door, and "ASTRO-THERM" heating tubes that allow fast recovery time, and lower frying temperatures

### SPECIFY TYPE OF GAS WHEN ORDERING.

### SPECIFY ALTITUDE WHEN ABOVE 2,000 ft.

## UTILITY INFORMATION - GAS:

- Ranges are supplied with 1-1/4" front manifold connection and a 1" or 3/4" capped rear manifold connection. For rear manifold connection, remove cap. Ranges are supplied with 3/4" gas pressure regulator. For 1-1/4" or 1" gas pressure regulator, see accessories. (Specify required front manifold cap and cover when ordering.)
- Required operating pressure: Natural Gas 5" W.C. minimum Propane Gas 10" W.C. minimum 14" W.C. maximum
- **Note:** This unit must be connected with the gas appliance regulator supplied.

JADE RANGE, LLC., A MIDDLEBY COMPANY • 2650 Orbiter Street • Brea, CA 92821 • PHONE: 800-884-5233 FAX: 714-961-2550 Note: In line with their policy to continually improve products, Jade reserves the right to change materials and specifications without notice. PRINTED IN USA