

TEM NO	
PROJECT _	
LOCATION	<u> </u>
DATE	QTY



# KSCB SERIES Chef Bases

### **MODELS**

- □ KSCB53
- □ KSCB60
- □ KSCB72
- □ KSCB84
- □ KSCB96

### **FEATURES**

#### CONSTRUCTION

- Designed to accomodate countertop cooking equipment
- Stainless steel top, front, sides and drip guard top
- Stainless steel interior
- Galvanized steel back and bottom
- Foamed-in-place with low ODP polyurethane insulation
- Wall thickness: 1.75"
- Full 3/4" marine drip guard to prevent spills from dripping over the edge
- Exterior digital thermometer
- 4" diameter casters
- Heavy-duty ergonomic handles

#### **DRAWERS**

- Stainless steel frames
- Supported on stainless steel telescoping drawer slides with stainless steel roller bearing wheels

- Drawer slides withstand maximum of 200 lbs. per drawer without deflection
- Upper and lower drawers accomodate 4" deep 12" x 20" pans
- Heavy-duty pan adapter bars supplied for full-size pans
- Pans not included
- Snap-in type vinyl magnetic gasket attached to each drawer for positive seal

#### REFRIGERATION

- Self-contained forced air refrigeration system metered by capillary tube
- Automatic defrost
- High humidity evaporator coils are coated to resist corrosion
- Removable front thermometer panel and grille for easy access to slide-out refrigeration system

- Refrigerant: R-134a
- Temperature range: 35° to 40°F (1.7° to 4.4°C)

#### WARRANTY

- Standard limited three year parts and labor
- Additional two year coverage on compressor part

## **OPTIONS**

- ☐ Full size stainless steel pans 4" x 20<sup>3</sup>/<sub>4</sub>"x 12<sup>3</sup>/<sub>4</sub>", 14 quart)
- ☐ Horizontal pan dividers (to accomodate 1/3 & 1/6 size pans)

## BID SPECIFICATIONS

Item no. KSCB\_ \_. Provide \_ Chef Base(s), Kool Star model no. KSCB

Chef base will feature stainless steel top, front, sides & drip guard top. Interior will be stainless steel with galvanized steel back and bottom. Base will be equipped with a full 3/4" marine drip guard, an exterior digital thermometer, and 4" diameter casters.

Drawers will feature stainless steel frames and will be supported on stainless steel telescoping drawer slides with stainless steel roller bearing wheels. Drawer slides to withstand maximum of 200 lbs. without deflection.

The refrigeration system will be selfcontained forced air type. Refrigerant will be R-134a. The temperature range will be

 $35^{\circ}$  to  $40^{\circ}$ F (1.7° to 4.4°C). System will be equipped with automatic defrost and coated evaporator coils.

Chef base to have standard limited three year parts and labor withadditional two year coverage on compressor part.

Chef base to be UL, C-UL and ETL Sanitation listed.







## TECHNICAL SPECIFICATIONS


	DIMENSIONS (in.)			DIMENSIONS (mm)					UNIT	NO. OF	NO. OF	CAP.	SHIP	SHIP WT.
MODEL	L	D	Н*	L	D	Н*	VOLTS	AMPS	H.P.	DRAWERS	PANS**	CU. FT.	CU. FT.	(LB/KG)
KSCB53	53	31	251/2	1340	787	648	115	3.3	1/5	2	6	9.8	30.1	230/105
KSCB60	60	31	251/2	1524	787	648	115	3.3	1/5	2	6	9.8	31.8	250/114
KSCB72	72	31	251/2	1791	787	648	115	3.3	1/5	4	8	14.3	39.4	340/155
KSCB84	84	31	251/2	2115	787	648	115	6.0	3/8	4	10	17.2	46.5	355/161
KSCB96	961/16	31	251/2	2438	787	648	115	6.0	3/8	4	12	21.4	53.6	390/177

<sup>\*</sup>Height includes casters. \*\*Full size 203/4" x 123/4" pans.






60" 3-1/2" KSCB60 ELEVATION VIEW




KSCB53 ELEVATION VIEW


KSCB53 PLAN VIEW


KSCB60 PLAN VIEW






KSCB72 PLAN VIEW








KSCB84 ELEVATION VIEW

KSCB84 PLAN VIEW

SIDE VIEW - ALL MODELS



96-1/16" 94-1/2" -29-7-16"

KSCB96 ELEVATION VIEW

KSCB96 PLAN VIEW

## **LISTINGS**

## **HOOKUP**

All models via plug in, 9 foot long flexible three wire 14 ga. cord with molded plug.



NOTE: Cabinet designed for optimum performance in air-conditioned area at 75°F ambient and 55% relative humidity. All specifications subject to change without notice.



