

STANDARD SERIES UNDERBAR DRAINBOARDS

MODEL: _____ PROJECT: _____ ITEM #: _____ QTY: _____

PRODUCT IMAGE



18-GS24 SHOWN

AVAILABLE IN 1800 or 2100 SERIES

STANDARD FEATURES

- **Drainboard**
20 gauge embossed stainless steel reinforced with welded braces every 6 inches. $\frac{3}{4}$ " radius on all vertical and horizontal edges
- **Front Apron**
22 gauge stainless steel clad over 20 gauge galvanized steel
- **Backsplash**
22 gauge stainless steel
- **Sides**
20 gauge stainless steel
- **Back and Bottom**
20 gauge galvanized steel
- **Legs**
1 $\frac{5}{8}$ " tubular 16 gauge galvanized steel with grey plastic bullet foot
- **Plumbing**
1" IPS drain connection

OPTIONAL ACCESSORIES

- **C-36** Upgrade: Stainless Steel Legs
- **C-39** Right End Side Splash
- **C-40** Left End Side Splash
- **C-47** Right End Return (Corner)
- **C-48** Left End Return (Corner)
- **S-"XX"** Single Speedrail ("XX" denotes 24, 30", or 36" or 48")
- **D-"XX"** Double Speedrail ("XX" denotes 24, 30", or 36")



CERTIFICATIONS:

APPROVED BY:

Due to our commitment to continued product improvement, specifications are subject to change without notice.

Printed in the USA

Krowne Metal Corporation

100 Haul Rd. Wayne, NJ 07470 • Toll Free: (800) 631-0442 • Fax: (973) 872-1129
sales@krowne.com • www.krowne.com • www.facebook.com/KrowneMetal • www.twitter.com/KrowneMetal




Rev. 09/2011
No. 4.8



STANDARD SERIES UNDERBAR DRAINBOARDS

MODEL: _____ PROJECT: _____ ITEM #: _____ QTY: _____




1800 SERIES



Model Numbers	Length Ⓐ	Left Side to Drain Ⓑ	Weight (lbs.)
18-GS12	1'-0"	6"	20
18-GS18	1'-6"	14"	26
18-GS24	2'-0"	20"	30
18-GS30	2'-6"	26"	35
18-GS36	3'-0"	32"	40
18-GS48	4'-0"	24"	50

MECHANICAL REQUIREMENTS: 1" IPS drain connection

2100 SERIES



Model Numbers	Length Ⓐ	Left Side to Drain Ⓑ	Weight (lbs.)
21-GS12	1'-0"	6"	25
21-GS18	1'-6"	14"	30
21-GS24	2'-0"	20"	40
21-GS30	2'-6"	26"	45
21-GS36	3'-0"	32"	50
21-GS48	4'-0"	24"	60

MECHANICAL REQUIREMENTS: 1" IPS drain connection



APPROVED BY: _____

CERTIFICATIONS: _____

Due to our commitment to continued product improvement, specifications are subject to change without notice.